CATALOGUE

Warehouse Equipment Products



(604) 614-3530

www.fleetmanconsulting.com

Ergo-Handle Carts

The Ergo-Handle Cart is constructed of heavy-duty steel to handle uniform loads up to 4,000 pounds. The patented ergonomic handle decreases fatigue by allowing the operator to easily maneuver the cart. Rolls on 2 rigid, 2 swivel 8" x 2" casters with roller bearings. Invertible bolt-on chrome ergonomic handle designed for individual height comfort and handling of long loads.

MODEL NUMBER	PLATFORM	SHELF CLEARANCE	TOP SHELF	UNIFORM	NET WT.
8" x 2" GLASS-FILLED-	SIZE (W x L)	GLEANANGE	HEIGHT	CAPACITY	(LBS.)
2-SHELF UNITS					
DH-PH4-2436	24" x 36"	22"	361/4"	4,000 lbs.	225
DH-PH4-2448	24" x 48"	22"	361/4"	4,000 lbs.	253
DH-PH4-2460	24" x 60"	22"	361/4"	4,000 lbs.	275
DH-PH4-2472	24" x 72"	22"	361/4"	4,000 lbs.	280
DH-PH4-3448	34" x 48"	22"	361/4"	4,000 lbs.	286
DH-PH4-3460	34" x 60"	22"	361⁄4"	4,000 lbs.	320
DH-PH4-3472	34" x 72"	22"	361/4"	4,000 lbs.	330
3-SHELF UNITS					
DH-PH4-2436-3	24" x 36"	9 ³ ⁄4"	361/4"	4,000 lbs.	270
DH-PH4-2448-3	24" x 48"	9¾"	36¼"	4,000 lbs.	288
MODEL	PLATFORM	SHELF	TOP SHELF	UNIFORM	NET WT.
NUMBER	SIZE (W x L)	CLEARANCE	HEIGHT	CAPACITY	(LBS.)
8" x 2" POLYURETHANE	CASTERS				
2-SHELF UNITS					
DH-PU2.4-2436	24" x 36"	22"	361/4"	3,600 lbs.	230
DH-PU2.4-2448	24" x 48"	22"	361/4"	3,600 lbs.	250
DH-PU2.4-3060	30" x 60"	22"	36¼"	3,600 lbs.	304
MODEL NUMBER	PLATFORM Size (W x L)	SHELF CLEARANCE	TOP SHELF Height	UNIFORM Capacity	NET WT. (LBS.)
8" x 2" MOLD-ON-RUB					(1201)
2-SHELF UNITS					
DH-MR2-2436	24" x 36"	22"	361/4"	2,400 lbs.	199
DH-MR2-2448	24" x 48"	22"	361/4"	2,400 lbs.	229
DH-MR2-3060	30" x 60"	22"	36¼"	2,400 lbs.	365
MODEL			SIZE	LIP	NET WT.
NUMBER	DESCR		(W x L)	HEIGHT	(LBS.)
DHPH-1236-UTS	OPTIONAL UT		12" x 36"	2"	42
DHPH-1248-UTS	OPTIONAL UT		12" x 48"	2"	52
DHPH-1260-UTS	OPTIONAL UT		12" x 60"	2"	62
DHPH-1272-UTS	OPTIONAL UT	ILITY SHELF	12" x 72"	2"	75

OPTIONAL FLOOR LOCK, model ERGO-FL

Stockpicker Trucks

Combine the mobility of a cart with the versatility of a step ladder with our Stockpicker Trucks. Convenient spring loaded step ladder holds the cart securely in place while a person is standing on the ladder. Crutch tip ladder prevents the cart from moving while stocking. Springs then return the ladder to the raised position once personnel exit the step. All shelves have a 2" lip turned up to prevent items from falling off. Standard casters are 4" x 2" mold-on-rubber, two rigid and two swivel with wheel brakes. Steel units are powder coated blue.

MODEL NUMBER	BOTTOM SHELF SIZE (W x L)	SHELF CLEARANCE	TOP SHELF Height	UNIFORM Cap./Shelf	TOTAL Uniform Cap.	NET WT. (LBS)
ALUMINUM CONST	TRUCTION					
2-SHELF UNITS						
SPA2-2236	22" x 36"	28"	355/8"	330 lbs.	660 lbs.	98
SPA2-2840	28" x 40"	28"	355/8"	330 lbs.	660 lbs.	135
SPA2-2848	28" x 48"	28"	355/8"	330 lbs.	660 lbs.	147
3-SHELF UNITS						
SPA3-2236	22" x 36"	131⁄2"	355/8"	330 lbs.	1,000 lbs.	125
SPA3-2840	28" x 40"	131⁄2"	355/8"	330 lbs.	1,000 lbs.	150
SPA3-2848	28" x 48"	131⁄2"	355/8"	330 lbs.	1,000 lbs.	180
STEEL CONSTRUC	TION					
2-SHELF UNITS						
SPS2-2236	22" x 36"	28"	355/8"	550 lbs.	1,000 lbs.	200
SPS2-2840	28" x 40"	28"	355/8"	550 lbs.	1,000 lbs.	210
SPS2-2848	28" x 48"	28"	355/8"	550 lbs.	1,000 lbs.	225
3-SHELF UNITS						
SPS3-2236	22" x 36"	131⁄2"	355/8"	550 lbs.	1,000 lbs.	260
SPS3-2840	28" x 40"	131⁄2"	355/8"	550 lbs.	1,000 lbs.	275
SPS3-2848	28" x 48"	131⁄2"	355/8"	550 lbs.	1,000 lbs.	298
LIPS DOWN ON TOP	SHELF, MODEL SPS-	LIPD				











model SPS2-2041-C

series SPA-HD

HI-FRAME

Steel Cantilever Stockpicker Truck

This unique cantilever design allows for oversized packages to fit conveniently on the bottom shelf without restricting access to the packages. Eliminate the need to move around a clumsy ladder and push a cart while trying to stock or unstock shelves. The step ladders are spring loaded to hold the cart securely in place while a person is standing on the ladder. Two rigid and two swivel 4" x 11/2" mold-on-rubber casters standard. Total uniform capacity is 440 lbs. per cart, uniformly loaded.

MODEL NUMBER	BOTTOM SHELF Size (W x L)	SHELF Clearance	TOP SHELF Height	UNIFORM Top Shelf Capacity	UNIFORM Bottom Shelf Capacity	NET WT. (LBS.)
SPS2-2041-C	201/2" x 415/8"	27 ⁷ /8"	36½"	110 lbs.	440 lbs.	110

Hi-Duty & Hi-Frame Stockpicker Trucks

These oversized units are perfect for large jobs. Ideal for oversized cartons, boxes, parts, and supplies. A spring loaded ladder for sure, safe climbing, and loading. Steps have non-skid footing with self-cleaning surface. Each unit features three shelves. Standard 4" x 2" mold-on-rubber casters, 2 rigid and 2 swivel with brake. Built of durable steel or aluminum construction. Steel units are powder coated a blue finish.

MODEL NUMBER	BOTTOM SHELF Size (W x L)	SHELF Clearance	TOP SHELF HEIGHT	UNIFORM Capacity Per Shelf	TOTAL Uniform Capacity	NET WT. (LBS.)
HI-DUTY STOCKPICK	ER TRUCKS					
ALUMINUM						
SPA-HD-2252	22" x 52"	13"	35½"	330 lbs.	500 lbs.	156
SPA-HD-2852	28" x 52"	13"	35½"	330 lbs.	500 lbs.	168
STEEL						
SPS-HD-2252	22" x 52"	13"	37¾"	500 lbs.	1,000 lbs.	230
SPS-HD-2852	28" x 52"	13"	37¾"	500 lbs.	1,000 lbs.	270
HI-FRAME STOCKPI	CKER TRUCKS					
STEEL						
SPS-HF-2252	22" x 52"	27"	631⁄2"	500 lbs.	1,000 lbs.	230
SPS-HF-2852	28" x 52"	27"	631⁄2"	500 lbs.	1,000 lbs.	270

Service Carts

All welded Service Carts made of steel or aluminum are ideal for transporting parts and boxes. A 2" lip is turned up on all shelves to prevent items from sliding off. Standard 4" x 2" mold-on-rubber casters, 2 rigid and 2 swivel with brake. Steel units are powder coated blue.

MODEL NUMBER	BOTTOM SHELF Size (W x L)	SHELF Clearance	TOP SHELF HEIGHT	UNIFORM Capacity Per Shelf	TOTAL Uniform Capacity	NET WT. (LBS.)
ALUMINUM CONS	TRUCTION					
2-SHELF UNITS						
SCA2-2236	22" x 36"	231/2"	31 ¹ /8"	330 lbs.	660 lbs.	61
SCA2-2840	28" x 40"	23 ½"	31 ¹ /8"	330 lbs.	660 lbs.	70
SCA2-2848	28" x 48"	231/2"	31 ¹ /8"	330 lbs.	660 lbs.	76
3-SHELF UNITS						
SCA3-2236	22" x 36"	15"	31 ¹ /8"	330 lbs.	660 lbs.	72
SCA3-2840	28" x 40"	15"	31 ¹ /8"	330 lbs.	660 lbs.	84
SCA3-2848	28" x 48"	15"	31 ¹ /8"	330 lbs.	660 lbs.	94
STEEL CONSTRUC	TION					
2-SHELF UNITS						
SCS2-2236	22" x 36"	23 ½"	39 ⁵ /8"	550 lbs.	1,000 lbs.	115
SCS2-2840	28" x 40"	231/2"	39 ⁵ /8"	550 lbs.	1,000 lbs.	136
SCS2-2848	28" x 48"	231/2"	395/8"	550 lbs.	1,000 lbs.	151
3-SHELF UNITS						
SCS3-2236	22" x 36"	15"	395/8"	550 lbs.	1,000 lbs.	144
SCS3-2840	28" x 40"	15"	395/8"	550 lbs.	1,000 lbs.	174
SCS3-2848	28" x 48"	15"	39 ⁵ /8"	550 lbs.	1,000 lbs.	197
LIP DOWN ON TOP S	ELF. MODEL SPS-LIPI					

Two-Tier Steel Service Cart

Heavy-duty two-tier service cart has a capacity of 1,100 lbs. per shelf and a total weight capacity of 2,200 lbs. Units roll smoothly on two rigid and two swivel 5" x 2" non-marking polyurethane casters. Steel construction with blue finish. Ships knock-down.

MODEL NUMBER	DECK SIZE (W x L)	TOP SHELF HEIGHT	LOWER SHELF HEIGHT	HANDLE HEIGHT	UNIFORM STATIC Capacity (LBS.)	NET WT. (LBS.)
STC-1835	18" x 35"	321/2"	81/2"	38"	2,200	71

COATED

HI-DUTY

STOCKPICKER series SPS-HD







CASTERS ARE NOT ATTACHED FOR SHIPPING PURPOSES (pgs. 203-208)

Unique two shelf design features three support legs to allow for easier access to bottom shelf. Attractive chrome plated ergonomic push handles are ideal for users of various heights. Two rigid and two locking swivel ball bearing poly casters 5" x 1¼" are standard. Mount swivel casters to the front of cart for lighter applications and to the rear for heavier applications. Optional bolt-on writing surface with hinged top for access to lockable storage box to hold supplies. The optional basket is ideal for extra carrying capacity. Fold-out design simplifies assembly. Ships knockdown. Assembly required. Steel construction.

MODEL NUMBER	DECK SIZE (W x L)	CAPACITY PER SHELF	UNIFORM STATIC Capacity (LBS.)	OVERALL SIZE (W x L x H)	NET WT. (LBS.)		
EASY-A-1836®	18" x 36"	660	1,200	18" x 41½" x 36"	70		
EASY-A-2436®	24" x 36"	660	1,200	24" x 41½" x 36"	80		
EASY-A-2448®	24" x 48"	660	1,200	24" x 53½" x 36"	90		
EASY-A-WT®	Optional Writing	g Table/Storage	BOX (Size 13"W x 11"E) x 9½"H)	27		
EASY-A-BSK®	Optional Wire S	Optional Wire Storage Basket					

Double & Triple Decker Hardwood Platform Carts

Minimize lifting and bending with this cart/portable work bench. Ideal for shipping areas, offices, and plant use, these economical carts are perfect for many of your applications. Constructed of 7/8" thick hardwood platform and removable steel push handle. 6" x 2" mold-on-rubber casters, two rigid and two swivel. Countersunk holes allow for a smooth deck surface. Ships knockdown.

MODEL NUMBER	DECK SIZE (W x L)	UNIFORM STATIC Capacity (LBS.)	DECK HEIGHT	NUMBER OF Shelves	NET WT. (LBS.)
DOUBLE DECKER					
VHPT/D-2448	24" x 48"	1,600	91⁄4" / 22"	2	193
VHPT/D-2754	27" x 54"	1,600	91⁄4" / 22"	2	217
VHPT/D-3060	30" x 60"	1,600	91⁄4" / 22"	2	233
VHPT/D-3672	36" x 72"	1,600	91/4" / 22"	2	288
TRIPLE DECKER					
VHPT/TD-2448	24" x 48"	1,600	91⁄4" / 22" / 421⁄4"	3	263
VHPT/TD-2754	27" x 54"	1,600	91⁄4" / 22" / 421⁄4"	3	297
VHPT/TD-3060	30" x 60"	1,600	91⁄4" / 22" / 421⁄4"	3	313
VHPT/TD-3672	36" x 72"	1,600	91/4" / 22" / 421/4"	3	365

Plastic Utility Service Carts

Constructed from durable yet lightweight structural foam plastic. Choose either 2 or 3 shelf design to accommodate your application. Deep 4" high lips prevent parts from rolling off. Ideal for mail rooms, shipping docks, grocery stores, warehouses, and inventory rooms. Includes two rigid and two swivel casters. Ships knockdown - assembly required.

MODEL NUMBER	DECK SIZE (W x L)	SHELF CAPACITY	UNIFORM STATIC Capacity (LBS.)	NUMBER OF SHELVES	NET WT. (LBS.)
PLSC-2-1731	17½" x 31"	275 lbs.	550 lbs.	2	35
PLSC-3-1731	17½" x 31"	183 lbs.	550 lbs.	3	53
PLSC-2-2436	24½" x 36"	275 lbs.	550 lbs.	2	47
PLSC-3-2436	24½" x 36"	183 lbs.	550 lbs.	3	65

Two & Three Shelf Plastic Platform Carts

Transport loads from workstation to workstation with these heavy-duty polyurethane Platform Carts. Available in either two or three shelf design. Ideal for shipping and receiving areas, maintenance departments, and general warehouse use. Handle height is 361/4". Uniform static capacity is 500 pounds. Rolls on (4) swivel 4" x 11/4" rubber casters. Ships knockdown.

MODEL NUMBER	DECK SIZE (W x L)	TOP DECK HEIGHT	MIDDLE DECK HEIGHT	LOWER DECK HEIGHT	NUMBER OF Shelves	NET WT. (LBS.)
PSC-1828-2®	18" x 28"	29"		5 ¾"	2	39
PSC-1828-3®	18" x 28"	29"	17½"	5 ³ ⁄4"	3	47

Double Tray/Double Basket Mail Cart

Quickly transport office mail and small package delivery throughout your office and warehouse. Two removable, lift-out baskets make delivery, collection and filing of materials easy and convenient. Comes with two file folder hanger runners that can be adjusted for letter or legal size hanging files. Excellent mobility on (4) 4" x 1¹/₄" swivel casters with rear brakes. Steel construction. Easy assembly,

MODEL	OVERALL SIZE	SHELF HEIGHT	UNIFORM STATIC	BASKET SIZE	NET WT.
NUMBER	(W x L x H)	W/O BASKETS	Capacity (LBS.)	(W x L x H)	(LBS.)
MAIL-55	18" x 31" x 39"	11" / 33"	200	17½" x 20" x 10"	



205

Industrial Carts & Dollies



EASY-A-WT

DOUBLE DECKER

model VHPT/D

TRIPLE DECKER model VHPT/TD



1) to Ship

48 Hours

-)to Ship







Lightweight tread plate deck is constructed of all welded aluminum. Rounded-edge platform protects walls from damage during transit. Includes one removable high-polished steel handle and two rigid and two swivel 5" x 2" poly-on-steel casters. Ideal for commercial and warehouse areas.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC Capacity (LBS.)	CASTER Type	NET WT. (LBS.)
ATP-2448	24" x 48"	10"	3,600	POLY-ON-STEEL	77
ATP-2460	24" x 60"	10"	3,600	POLY-ON-STEEL	90
ATP-3048	30" x 48"	10"	3,600	POLY-ON-STEEL	83
ATP-3060	30" x 60"	10"	3,600	POLY-ON-STEEL	94
ATP-3672	36" x 72"	10"	3,600	POLY-ON-STEEL	114

HANDLE DESIGN MAY VARY FROM WHAT IS SHOWN

Heavy-Duty Extruded Aluminum Platform Trucks

These all welded aluminum trucks are built to handle your heaviest loads. Includes one removable high-polished steel handle, additional handle available. Rolls smoothly on two rigid and two swivel 8" x 2" glass-filled nylon casters. Ideal for industrial and warehouse areas.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC Capacity (LBS.)	CASTER Type	NET WT. (LBS.)
EFHD-2448	24" x 48"	10¾"	4,800	GFN*	145
EFHD-3048	30" x 48"	10¾"	4,800	GFN*	152
EFHD-3060	30" x 60"	10¾"	4,800	GFN*	176
EFHD-3672	36" x 72"	10¾"	4,800	GFN*	190

HANDLE DESIGN MAY VARY FROM WHAT IS SHOWN

*GLASS-FILLED NYLON

Aluminum Channel Platform Trucks

Rugged dependable service at an economical price. Extruded deck sections are engineered for high load capacity, durability, and shock resistance. All aluminum construction. Includes one removable high-polished steel handle and two rigid and two swivel 5" x 2" poly-on-steel casters. Ideal for commercial, industrial, and warehouse areas.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC Capacity (LBS.)	CASTER Type	NET WT. (LBS.)
SDD-2448	24" x 48"	101⁄2"	3,600	POLY-ON-STEEL	84/UPS
SDD-3048	30" x 48"	10½"	3,600	POLY-ON-STEEL	88/UPS
SDD-3060	30" x 60"	10½"	3,600	POLY-ON-STEEL	94
SDD-3672	36" x 72"	10½"	3,600	POLY-ON-STEEL	109

HANDLE DESIGN MAY VARY FROM WHAT IS SHOWN

Aluminum Sheet Deck Platform Trucks

Tough but lightweight, this truck is made of smooth aluminum for durability. Includes one removable high-polished steel handle. Two rigid and two swivel 5" x 2" poly-on-steel casters are standard. Ideal for commercial, industrial, and warehouse areas.

MODEL NUMBER	DECK SIZE (W x L))	DECK HEIGHT	UNIFORM STATIC Capacity (LBS.)	CASTER TYPE	NET WT. (LBS.)
ASD-2448	24" x 48"	10"	3,600	POLY-ON-STEEL	77/UPS
ASD-2460	24" x 60"	10"	3,600	POLY-ON-STEEL	86/UPS
ASD-3048	30" x 48"	10"	3,600	POLY-ON-STEEL	83
ASD-3060	30" x 60"	10"	3,600	POLY-ON-STEEL	94
ASD-3672	36" x 72"	10"	3,600	POLY-ON-STEEL	114

HANDLE DESIGN MAY VARY FROM WHAT IS SHOWN

Fold-Up Aluminum Platform Truck

Telescoping aluminum frame has dual length platform; 25" extended and $16\frac{1}{2}$ " retracted. Easy steering with 4" x 1" hard rubber casters, two rigid and two swivel. Folded dimensions are 16"W x 20"L allowing the truck to fit into tight spaces for storage. Handle height is $33\frac{1}{2}$ " extended and $26\frac{1}{2}$ " retracted. Ideal for delivery, repair personnel, frequent travelers and salespeople.

MODEL	OVERALL	DECK	UNIFORM STATIC	CASTER	NET WT.
NUMBER	SIZE (W x L)	Height	Capacity (LBS.)	TYPE	(LBS.)
FAPT-1628	16" x 28"	61⁄2"	300	HARD RUBBER	









206

INDUSTRIAL GARTS & DOLLIES

Aluminum Folding Handle Platform Trucks

For safe transportation of stacks of paper, small parts and other lightweight equipment. Ideal for maintenance rooms, offices, schools, hospitals, etc. Plastic corner protectors enhance durability and protect surroundings. Rugged aluminum construction with single or dual folding handle design.

MODEL NUMBER	HANDLE Type	DECK SIZE (W x L x H)	UNIFORM STATIC Capacity (LBS.)	CASTER SIZE	NET WT. (LBS.)
RUBBER CASTE	RS				
AFT-30	SINGLE	18½" x 30" x 6¾"	400	4"	20
AFT-36	SINGLE	24" x 36" x 7 ³ /8"	600	5"	35
AFT-48	SINGLE	24" x 48" x 7 ³ /8"	600	5"	40
AFT-60	DUAL	30" x 60" x 7 ³ /8"	800	5"	60
NON-MARKING	POLYURETHAN	IE CASTERS			
AFT-30-NM	SINGLE	18½" x 30" x 73/8"	400	5"	20
AFT-36-NM	SINGLE	24" x 36" x 8 ³ /8"	600	6"	35
AFT-48-NM	SINGLE	24" x 48" x 8 ³ / ₈ "	600	6"	40
AFT-60-NM	DUAL	30" x 60" x 8 ³ /8"	800	6"	60

Aluminum Platform Trucks with Folding Handle

Move supplies, forms, files, office equipment, or almost anything around the office or shop. Compact size is ideal for use on delivery vehicles. Each model features a steel handle which folds down for storage. Equipped with easy rolling 4" x 1" rubber casters, two rigid and two swivel.

MODEL	DESCRIPTION	DECK SIZE	DECK	UNIFORM STATIC	NET WT.
NUMBER		(W x L)	HEIGHT	Capacity (LBS.)	(LBS.)
FAT-1829®	ALUMINUM	18" x 29"	61⁄2"	330	23

Steel Platform Trucks

Solid, smooth steel deck is all welded and features structural reinforcement underneath for extra strength. Includes one removable high-polished steel handle and rolls smoothly on two rigid and two swivel casters. Series SPT comes standard with a floor lock and a durable blue powder coat finish.

MODEL NUMBER	DECK SIZE (W x L)	DECK Height	UNIFORM STATIC Capacity (LBS.)	CASTER Size / Type	NET WT. (LBS.)
STEEL PLATFORM TR	UCKS				
SPT-2448	24" x 48"	121⁄4"	3,600	8" x 2" GFN*	195
SPT-3060	30" x 60"	121/4"	3,600	8" x 2" GFN*	216
SPT-3672	36" x 72"	121/4"	3,600	8" x 2" GFN*	250
ECSPT-2448	24" x 48"	11 ⁷ /8"	2,000	6" x 2" RUBBER	120
STEEL PLATFORM TR	UCKS WITH SCAI				
SPT-2448-SCL	24" x 48"	15"	3,600	8" x 2" GFN*	263
SPT-3060-SCL	30" x 60"	15"	3,600	8" x 2" GFN*	327
SPT-3672-SCL	36" x 72"	15"	3,600	8" x 2" GFN*	379
WRITING TABLE					
WT-TBL	WRITING TA	BLE measur	res 10½"W x 13"H wit	h a 1" lip	4

*GLASS-FILLED NYLON

Pneumatic Tire Steel Platform Trucks

Travel over rough terrain with these steel platform trucks. Ideal for nurseries, farms, and warehouses. Units have 12" x 4" (2) swivel and (2) rigid casters. Durable blue powder coat finish standard.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC Capacity (LBS.)	CASTER Type	NET WT. (LBS.)
PNU-2448	24" x 48"	18¼"	1,500	PNEUMATIC	228
PNU-3060	30" x 60"	18¼"	1,500	PNEUMATIC	242
PNU-3672	36" x 72"	18¼"	1,500	PNEUMATIC	276

Flat Bed Cart

Heavy duty steel platform cart provides long term service. Removable handle. Rolls on (4) 5" swivel and (2) 8" poly rigid casters. Center caster provides great maneuverability. Ideal for industrial, commercial and warehouse use.

MODEL	OVERALL SIZE	UNIFORM STATIC	CASTER	CASTER	NET WT.
NUMBER	(W x L x H)	Capacity (LBS.)	SIZE	Type	(LBS.)
FLAT-C	30" x 60" x 11¾"	2,000	(4) 6" & (2) 8"	POLY	125



48 Hours

48 Hours



207

48 Hours

to Ship



Hardwood Platform Trucks

Hardwood Platform Trucks are the economical solution to your material handling needs. Constructed of ⁷/₈" thick hardwood, these platform trucks have a maximum capacity of 1,600 pounds. Units roll smoothly on 6" x 2" mold-on-rubber casters, two rigid and two swivel. Casters and removable steel push handle are bolted on. Countersunk holes allow for a smooth deck surface.

MODEL NUMBER	DECK SIZE (W x L)	DECK Height	UNIFORM STATIC Capacity (LBS.)	CASTER TYPE	NET WT. (LBS.)
HARDWOOD DECK					
VHPT-2448*	24" x 48"	9 ½"	1,600	MOLD-ON-RUBBER	73
VHPT-2754*	27" x 54"	9 ½"	1,600	MOLD-ON-RUBBER	90
VHPT-3060*	30" x 60"	9 ½"	1,600	MOLD-ON-RUBBER	98
VHPT-3672	36" x 72"	9 ½"	1,600	MOLD-ON-RUBBER	167
HARDWOOD DECK V	VITH STEEL FRA	ME			
VHPT/S-2448	24" x 48"	9 ¾"	1,600	MOLD-ON-RUBBER	131
VHPT/S-2754	27" x 54"	9¾"	1,600	MOLD-ON-RUBBER	138
VHPT/S-3060	30" x 60"	9¾"	1,600	MOLD-ON-RUBBER	160
VHPT/S-3672	36" x 72"	9 ¾"	1,600	MOLD-ON-RUBBER	173

HANDLE DESIGN MAY VARY FROM WHAT IS SHOWN

(4) 8" x 2" PNEUMATIC CASTERS (CAPACITY 1,200 LBS.), MODEL VHPT-PNU

Plastic Platform Trucks with Fold Down Handle

Tough, high impact-resistant plastic construction is virtually maintenance free. Industrial grade plastic deck will not rust, dent, chip, or discolor. A ¹/₂" lip runs along the perimeter of the deck to help retain cargo. The steel 36" high steel handle folds down for storage. Units roll smoothly on two rigid and two swivel poly-on-poly casters.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC Capacity (LBS.)	CASTER SIZE	NET WT. (LBS.)
FPT-1624	15¾" x 23¾"	51⁄4"	250	4" x 1"	14
FPT-1830	18" x 27¾"	61⁄2"	250	4" x 1¼"	32
FPT-2133	21" x 33"	61⁄2"	500	4" x 1¼"	36
FPT-2537	25" x 37"	8"	500	6" x 1½"	41

Fold-Flat Plastic Cart

Unique cart folds completely flat for storage - telescopic handle folds down and casters fold up. Handle is adjustable to three different heights and features a cushion grip for comfort. Deck includes non-slip rubber grips and hand holes for easy carrying. Carts roll on two rigid and two swivel poly casters. Cart is constructed from plastic, steel and aluminum components.

MODEL	DECK SIZE	DECK	UNIFORM STATIC CAPAC-	CASTER	NET WT.
NUMBER	(W x L)	Height	ITY (LBS.)	SIZE	(LBS.)
FF-FPT-1627®	16¼" x 26¾"	71/4"	300	4" x 1"	

Heavy-Duty Plastic Platform Trucks

Heavy-duty plastic truck will not rust, discolor, or warp. Maintenance free and easy to clean. Honeycomb construction is reinforced for longer life. Extra square steel tube underneath platform to reinforce deck strength. Units roll smoothly on 6" x 2" polyurethane casters. The four wheel cart has two rigid and two swivel casters, while the 6 wheel cart has 4 swivel and two rigid casters. Handle height 38".

MODEL NUMBER	DECK SIZE (W x L)	DECK Height	UNIFORM STATIC Capacity (LBS.)	NUMBER OF CASTERS	NUMBER OF HANDLES	NET WT. (LBS.)
PPT-2-41	30" x 60"	71⁄2"	2,000	4	1	137
PPT-2-42	30" x 60"	71⁄2"	2,000	4	2	141
PPT-3-61	30" x 60"	71⁄2"	3,000	6	1	148
PPT-3-62	30" x 60"	71⁄2"	3,000	6	2	152

Versatile Platform Truck with Fold Down Handle

Transport products quickly and easily in commercial or industrial applications with our Versatile Platform Truck. Adjustable handle for pushing or pulling applications, folds down for storage. Will not rust, chip, or dent. Unit rolls smoothly on polyurethane casters.

	MODEL NUMBER	DECK SIZE (W x L x H)	HANDLE HEIGHT PULLING/PUSHING	UNIFORM STATIC CAPACITY (LBS.)	CASTER SIZE	NET WT. (LBS.)
	PC-25®	201/2" x 311/2" x 31/2"	295/8" / 331/2"	250	3"	22
48 Hours	PC-60®	20½" x 31½" x 6"	355/8" / 38"	600	5"	25
()to Ship						

series VHPT/S





48 Hours



Nesting Platform Cart

This steel platform truck is nestable to save valuable warehouse storage space. Ideal for warehouses, shipping and receiving areas, lumber retailers, mail rooms, and other places where multiple platform trucks are needed. The first cart requires a 30"W x 48"L floor space - each additional truck only adds 12" to the length. Durable powder coat finish.

MODEL	DECK SIZE	UNIFORM STATIC	CASTER	CASTER	NET WT.
NUMBER	(W x L)	Capacity (LBS.)	SIZE	TYPE	(LBS.)
NPCT	24" x 48"	1,500	6" x 2"	RUBBER	140

Corner and Surface Guards / Bumpers

Reduce damage to walls, furniture and machinery from carts and platform trucks impact. Thermoplastic rubber construction with steel insert provides impact absorption. Easily attaches to any steel, aluminum, wood, or plastic surface. Mounting hardware not included.

ТҮРЕ	MODEL NUMBER	STYLE	WIDTH	LENGTH	HEIGHT	THICKNESS	QTY. PER Carton	NET WT. (LBS.)
Α	CB-1	CORNER	3 ¹ /8"	3 ¹ /8"	⁵ /8"	⁵ /8"	28	6
B	CB-2	CORNER	3 ¹⁵ /16"	3 ¹⁵ /16"	1 ¹ /16"	1 ¹ /16"	16	3
C	CB-3	CORNER	4 ¹ /4"	4 ¹ /4"	1 ¹ /16"	1 ¹ /16"	12	4
D	CB-4	CORNER	4"	4"	1"	⁷ /8"	20	6
E	SB-12	EDGE		12"	1 ³ /16"	1 ³ /16"	12	6
F	EB-1	EDGE	1 ¹ /16"	240"	⁵ /16"	⁵ /32"	1	1
G	RB-1	ROUND	3 ¹ /4"	DIAMETI	ER, ⁵ /16"	BORE	16	3
Н	RB-2	ROUND	<u>5" </u> [DIAMETE	R, ⁷ /16" B	ORE	16	3

Nestable Multi-Use Cart with Brake

This cart rolls easily on its 6" polyurethane wheels. Brakes automatically lock when cart handle is not squeezed. Ideal in airports, malls, shipping and receiving areas.

MODEL	UNIFORM	OVERALL SIZE	CASTER	CASTER	NET WT.
NUMBER	Capacity	(W x D x H)	SIZE	TYPE	(POUNDS)
LUG-B	550 LBS.	261/2" x 391/2" x 39"	6"	POLY	45

Nestable Wire Carts

Portable lightweight mesh carts are nestable to minimize storage space. Steel construction with zinc-plated finish to resist rust. Wheels are non-marking poly-on poly. Each cart ships fully assembled and ready to use.

MODEL NUMBER	OVERALL SIZE (W x L x H)	UNIFORM STATIC Capacity (LBS.)	CASTER TYPE	NET WT. (LBS.)
WIRE-S	17½" x 36 ⁷ /16" x 40¾"	90	ALL SWIVEL	60
WIRE-L	28¾" x 59¼" x 36¾"	275	RIGID & SWIVEL	92
WIRE-M	28¾" x 52" x 43¼"	90	ALL SWIVEL	59

Landscape, Nursery & Agriculture Carts

Transport plants, flowers, trees, shrubs, rocks, and similar materials or parts with our full line of Landscape Carts. These carts are rugged and easy to maneuver with their large pneumatic tires. All carts have mesh sides and bottoms to allow dirt, small rocks, and water to drain through. Steel construction. All carts ship knockdown. Assembly required.



INDUSTRIAL GARTS & DOLLIES

209

model NPCT

New 2

POWDER

G & H

model LUG-B

model WIRE-S

48 Hours

to Ship

model WIRE-S

48 Hours



POLY-ON-STEEL



STEEL



GLASS-FILLED NYLON



PHENOLIC



HARD RUBBER



URETHANE SOLID FOAM

UFBL-10-WHL-58®

		In	dustrial C	asters		
MODEL NUMBER	CASTER Size	OVERALL Height	TOP PLATE Size	STYLE	UNIFORM Capacity	NET WT. (LBS.)
MOLD-ON-RUBBER						
MR-4/2-S®	4" x 2"	5½"	4" x 4½"	SWIVEL	350	7
MR-4/2-R®	4" x 2"	51/2"	4" x 4½"	RIGID	350	6
MR-4/2-SWB®	4" x 2"	5½"	4" x 4½"	SWIVEL (WITH BRAKE)	350	6
MR-6/2-S®	6" x 2"	71/2"	4" x 4½"	SWIVEL	450	10
MR-6/2-R⊛	6" x 2"	71/2"	4" x 4½"	RIGID	450	8
MR-8/2-S®	8" x 2"	91⁄2"	4" x 4½"	SWIVEL	500	12
MR-8/2-R®	8" x 2"	9 ½"	4" x 4½"	RIGID	500	10
POLY-ON-STEEL						
PU-5/2-S®	5" x 2"	6½"	4" x 4½"	SWIVEL	1200	8
PU-5/2-R®	5" x 2"	61⁄2"	4" x 4½"	RIGID	1200	6
PU-5/2-SWB®	5" x 2"	61⁄2"	4" x 4½"	SWIVEL (WITH BRAKE)	1200	8
PU-6/2-S®	6" x 2"	71/2"	4" x 4½"	SWIVEL	1200	10
PU-6/2-R®	6" x 2"	71/2"	4" x 4½"	RIGID	1200	10
PU-8/2-S®	8" x 2"	9 ½"	4" x 4½"	SWIVEL	1250	14
PU-8/2-R®	8" x 2"	9 ½"	4" x 4½"	RIGID	1250	13
PU-8/2-SWB®	8" x 2"	9 ½"	4" x 4½"	SWIVEL (WITH BRAKE)	1250	19
STEEL	ļ					ļ
SS-5/2-S®	5" x 2"	6½"	4" x 4½"	SWIVEL	1000	10
SS-5/2-R®	5" x 2"	6½"	4" x 4½"	RIGID	1000	8
SS-6/2-S®	6" x 2"	71⁄2"	4" x 4½"	SWIVEL	1200	11
SS-6/2-R®	6" x 2"	71/2"	4" x 4½"	RIGID	1200	10
SS-8/2-S⊛	8" x 2"	91⁄2"	4" x 4½"	SWIVEL	1250	14
SS-8/2-R℗	8" x 2"	91⁄2"	4" x 4½"	RIGID	1250	13
GLASS-FILLED NYLON	ļ					
GFN-4/2-S☉	4" x 2"	51/2"	4" x 4½"	SWIVEL	800	6
GFN-4/2-R [®]	4" x 2"	51/2"	4" x 4½"	RIGID	800	5
GFN-4/2-S-SWB®	4" x 2"	<u>51/2"</u>	4" x 4½"	SWIVEL (WITH BRAKE)	800	6
GFN-6/2-S®	6" x 2"	71/2"	4" x 4½"	SWIVEL	1200	10
GFN-6/2-R®	6" x 2"	71/2"	4" x 4½"	RIGID	1200	7
GFN-8/2-S®	8" x 2"	9½"	4" x 4½"	SWIVEL	1250	10
GFN-8/2-R®	8" x 2"	9½"	4" x 4½"	RIGID	1250	7
GFN-8/2-S-SWB®	8" x 2"	9½"	4" x 4½"	SWIVEL (WITH BRAKE)	1250	11
GFN-8/2-S-4PSL®	8" x 2"	9½"	4" x 4½"	SWIVEL (W/4 POSITION LOCK)	1250	11
GFN-8/2-S-TTL®	8" x 2"	91⁄2"	4" x 4½"	SWIVEL (WITH TOTAL LOCK)	1250	13
PHENOLIC DUE DO DO	0" x 0"	101/ "	41/ " x C1/ "	SWIVEL	2500	00
PH-F-8/3-S®	8" x 3" 8" x 3"	10½" 10½"	4½" x 6¼" 4½" x 6¼"		2500 2500	28 29
PH-F-8/3-S-4PSL⊕ HARD RUBBER	0 X 3	1072	4/2 X 0/4	SWIVEL (W/4 POSITION LOCK)	2300	29
HR-3/1.25-S®	3" x 1¼"	3¾"	3 ¹ /8" x 4 ¹ /8"	SWIVEL	275	4
HR-3/1.25-S®	3 x 1 ⁷ / ₄	3% 4½"	3 ¹ /8" x 4 ¹ /8"	SWIVEL	300	4
POLY-ON-POLY	4 X 1 74	472	3 /8 X 4 /8	SWIVEL	300	4
PD-4-1.25-S®	4" x 1¼"	5½"	2¾" x 3¾"	SWIVEL	300	3
PP-4-1.25-S®	4 x 1 ⁷ / ₄	5½"	2 ³ /4" x 3 ³ /4"	RIGID	300	3
PP-4-1.25-TTL®	4 x 1 ⁷⁴ 4" x 1 ¹ /4"	5½"	2 ³ /4" x 3 ³ /4"	SWIVEL (WITH TOTAL LOCK)	300	3
URETHANE SOLID FOAM		J/2	L/4 AU/4		000	5
UFBK-10-WHL-58®			8" BEARING	BLACK	300	4
UFRD-10-WHL-58®			BEARING	RED	300	4
UFYL-10-WHL-58®			BEARING	YELLOW	300	4
				TELLOW	300	+



Shock-Absorbing Wheels

The special design for Shock Absorption properties prevents wheels from bouncing like standard pneumatic wheels. Ideal for transporting loads downstairs. Solid black molded rubber tread will never go flat. Steel hubs for maximum strength. Precision bearings with 5%" inside diameter.

10" HIGH WITH 5/8" BEARING



MODEL NUMBER	DIAMETER	HUB STYLE	UNIFORM STATIC CAPACITY (POUNDS)	NET WT. (POUNDS)
SAW-10	10"	OFFSET - FOR HAND TRUCKS	330	6
SAW-16	16"	SYMMETRIC - FOR WHEEL BARREL	330	14

BLUE

300

4

Luggage Cart & Deluxe Platform Truck

This is a durable and attractive trucks built for function and style. Great for hotels, stores, and other commercial applications. Carpeted platform to prevent scratching of delicate items. Overall height 72". Units roll smoothly with poly-on-poly casters.

MODEL NUMBER	DECK SIZE (W x L x H)	UNIFORM STATIC Capacity (LBS.)	OVERALL HEIGHT	NET WT. (LBS.)
LUG-C	25¾" x 49" x 11¼"	600	72"	105
DELUXE-C	25¾" x 49½" x 8½"	600	36 ³ /8"	65

Foldaway Hand Truck

Designed for everyday all purpose use. The handle and wheels fold up quickly and easily allowing you to store it in tight spaces such as trunks of cars, under tables, or in closets.

MODEL	FOLDED SIZE	SIZE UNFOLDED	UNIFORM	NET WT.
NUMBER	(W x L x H)	(W x L x H)	Capacity	(POUNDS)
FHC-250	19" x 2¾" x 26"	19" x 17" x 40½"	250	16

4 Wheel Pneumatic/Hard Rubber Hand Truck

The most versatile and easy moving hand truck available. The 4 wheel design, 2 pneumatic and 2 hard rubber, allows the operator to easily move and position awkward loads. The weight and size of the load determine how much the hand truck rubber wheels are utilized. Ideal on rough floors and with awkward heavy loads.

MODEL	NOSE PLATE	OVERALL SIZE	UNIFORM	NET WT.
NUMBER	(W x D)	(W x D x H)	Capacity (LBS)	(POUNDS)
SPHT-500S-DW	22" x 7"	22" x 19" x 52"	600	75

Fiber/Nylon Hand Truck

Transport lightweight loads with this Fiber/Nylon Hand Truck. The unique construction is stronger than steel, yet lighter and more cost effective than aluminum. The $10" \ge 3\frac{1}{2}"$ pneumatic wheels provide a smooth ride and years of durability. Uniform static capacity is 500 pounds.

MODEL	NOSE PLATE	UNIFORM CAPACITY	OVERALL SIZE	NET WT.
NUMBER	(W x D)	(POUNDS)	(W x D x H)	(POUNDS)
FNHT-500	14" x 7"	500	20" x 48"	26

Site Cart/Truck

This large cart with big wheels works great to move items around in rough terrain. Landscaping is easier due to the oversized nose plate (holds scrub balls for transport). The wheels are 16" x $4\frac{1}{2}$ ". Welded steel construction with powder coat yellow finish. Uniform static capacity is 600 lbs.

MODEL NUMBER	NOSE PLATE (W x D)	OVERALL SIZE (W x D x H)	WHEEL STYLE	NET WT. (POUNDS)
SITE-C	24" x 13"	34¼" x 23" x 58"	PNEUMATIC	70
SITE-C-FF	24" x 13"	34¼" x 23" x 58"	FOAM-FILLED	70

Convertible Hand Trucks

The Aluminum & Steel Convertible Hand Trucks are versatile wonders. These hand trucks can work in both the vertical and horizontal positions. The task of transporting smaller crates or long narrow boxes is now simplified. These carts roll smoothly on 10" x 3½" rigid pneumatic and 4" x 1" swivel solid rubber casters. Ships knockdown.



MODEL NUMBER	DESCRIPTION	NOSE PLATE (W x D)	UNIFORM Capacity (LBS.)	OVERALL SIZE (W x D x H)	NET WT. (POUNDS)
CAHT-500	ALUMINUM	18" x 7¼"	500	20½" x 18 ⁷ /8" x 51½"	41 (UPS)
			650	20½" x 46½" x 40½"	
DSHT-500-PN	STEEL	13¾" x 7½"	500	22" x 19" x 49"	30 (UPS)
			500	22" x 42" x 36"	
CSHT-500	STEEL	10¼" x 7½"	500	19½" x 20" x 57¾"	69
			750	19½" x 42" x 37"	
	NUMBER CAHT-500 DSHT-500-PN	NUMBER DESCRIPTION CAHT-500 ALUMINUM DSHT-500-PN STEEL	NUMBER DESCRIPTION (W x D) CAHT-500 ALUMINUM 18" x 7¼" DSHT-500-PN STEEL 13¾" x 7½"	NUMBER DESCRIPTION (W x D) CAPACITY (LBS.) CAHT-500 ALUMINUM 18" x 7¼" 500 DSHT-500-PN STEEL 13¾" x 7½" 500 CSHT-500 STEEL 10¼" x 7½" 500	NUMBER DESCRIPTION (W x D) CAPACITY (LBS.) (W x D x H) CAHT-500 ALUMINUM 18" x 7¼" 500 20½" x 18 ⁷ /s" x 51½" DSHT-500-PN STEEL 13¾" x 7½" 500 22" x 46½" x 40½" DSHT-500 STEEL 13¾" x 7½" 500 22" x 19" x 49" 500 22" x 42" x 36" 20% 20% 20%

211



model LUG-C

48 Hours



FIBER/NYLON model FNHT-500

SITE CART/TRUCK model SITE-C



48 Hours Ito Ship

STEEL

ALUMINUM model DHHT-500S model DHHT-500A



ALUMINUM NOSE PLATE GALVANIZED FINISH model DHHT-500A-ANP SPHT-500S



APHT-500A



Dual Handle Hand Trucks

Maximize control for different loads with our Dual Handle Hand Trucks. These hand trucks can transport boxes or crates wherever they are needed. Transport loads smoothly and evenly over rough or uneven floors. Ships knockdown. Choose steel or aluminum, available with pneumatic or solid rubber wheels.

STEEL DUAL HANDLE HAND TRUCKS

MODEL	NOSE PLATE	UNIFORM	OVERALL SIZE	NET WT.	
NUMBER	(W x D)	CAPACITY	(W x D x H)	(POUNDS)	
10" x 2" HARD RUBBER WHEELS					
DHHT-500S-HR	13¾" x 6½"	500	21" x 17½" x 44½"	36	
10" x 3½" PNEUMATIC WHEELS					
DHHT-500S	13¾" x 6½"	500	22½" x 17½" x 44½"	36	

ALUMINUM DUAL HANDLE HAND TRUCKS

MODEL NUMBER	NOSE PLATE (W x D)	UNIFORM Capacity	OVERALL SIZE (W x D x H)	NET WT. (POUNDS)		
	10" x 2" H	IARD RUBBER WH	IEELS			
DHHT-500A-HR*	14" x 7¼"	500	20" x 18½" x 52"	36		
DHHT-500A-ANP-HR*	18" x 7½"	500	20" x 18½" x 52"	34		
10" x 3½" PNEUMATIC WHEELS						
DHHT-500A*	14" x 7¼"	500	20" x 18½" x 52"	32		
DHHT-500A-ANP*	14" x 7¼"	500	20" x 18½" x 52"	30		

"P" Handle Hand Trucks

The "P" style hand trucks are ideal for transporting heavy and awkward loads. These trucks work well for the user that needs to free up one hand. The "P" shaped handle makes the truck easy to steer and maneuver.

STEEL "P" HANNI E HANN TRUCKS

SIEEL F HANDLE HAND	INUGRƏ			
MODEL	NOSE PLATE	UNIFORM	OVERALL SIZE	NET WT.
NUMBER	(W x D)	CAPACITY	(W x D x H)	(POUNDS)
	10" x 2" HARI	D RUBBER WHEELS		
SPHT-500S-HR	13¾" x 7½"	500	21" x 18" x 52"	51
SPHT-500S-HD-HR*	22" x 7"	600	22" x 19" x 52"	64
	10" x 3½" PN	IEUMATIC WHEELS		
SPHT-500S	13¾" x 7½"	500	21" x 18" x 52"	37
SPHT-500S-HD*	22" x 7"	600	22" x 19" x 52"	35
	13" x 4" PN	EUMATIC WHEELS		
SPHT-600S-IND	14" x 7"	600	22" x 22" x 52"	37
*SHIPS TRUCK ONLY				

ALUMINUM "P" HANDLE HAND TRUCKS

MODEL	NOSE PLATE	UNIFORM	OVERALL SIZE	NET WT.	
NUMBER	(W x D)	CAPACITY	(W x D x H)	(POUNDS)	
10" x 2" HARD RUBBER WHEELS					
APHT-500A-HR	14" x 7½"	300	20" x 19" x 50½"	46	
10" x 3½" PNEUMATIC WHEELS					
APHT-500A	14" x 7¼"	500	20" x 18½" x 53"	32	

STAINLESS STEEL "P" HANDLE HAND TRUCKS

MODEL	NOSE PLATE	UNIFORM	OVERALL SIZE	NET WT.	
NUMBER	(W x D)	CAPACITY	(W x D x H)	(POUNDS)	
	10" x 2" HARI	D RUBBER WHEELS	S		
SPHT-500-HD-SS-HR*	22" x 7"	600	22" x 19" x 52"	66	
SPHT-500-SS-HR	13¾" x 7½"	500	21" x 18" x 52"	51	
10" x 3½" PNEUMATIC WHEELS					
SPHT-500-HD-SS	22" x 7"	600	22" x 19" x 52"	51	
SPHT-500-SS	13¾" x 7½"	500	21" x 18" x 52"	37	
*SHIPS TRUCK ONLY					

AXLE AND WHEEL HUB NOT STAINLESS STEEL

Moving Pad with Velcro Straps for Hand Trucks

Minimize scratches and damage to your belongings. Durable yet attractive pads fit most hand trucks with nose plate up to 14" wide. Two velcro wraps and one velcro nose wrap. Easy to install.

MODEL	DESCRIPTION	OVERALL SIZE	NET WT.
NUMBER		(W x H)	(POUNDS)
QPC-HT	MOVING PAD FOR HAND TRUCK	16" x 55"	3



Deluxe Aluminum Hand Trucks

Maximize control for different types of loads. These hand trucks can transport boxes wherever they are needed. Transport loads smoothly and evenly over rough or uneven floors. 10" x 3¹/₂" pneumatic tires are standard on all hand trucks. 10" x 2¹/₂" industrial solid rubber tires also available. The convertible hand truck has 10" x 3¹/₂" pneumatic tires and 5" x 1¹/₄" poly-on-steel swivel casters. Optional stair guides available.













model ALUM-P

model ALUM-H

model ALUM-LOOP

model ALUM-LOOP-H

model ALUM-CONV-B

	MODEL NUMBER	DESCRIPTION	NOSE PLATE (W x D)	UNIFORM Capacity (LBS.)	OVERALL SIZE (W x D x H)	NET WT. (POUNDS)
	ALUM-P®	"P" HANDLE	14" x 7¼"	500	20" x 18½" x 53"	25
	ALUM-H®	DUAL HANDLE	14" x 7¼"	500	20" x 18½" x 52"	25
	ALUM-LOOP ©	LOOP HANDLE	14" x 7¼"	500	20" x 18½" x 49¼"	27
	ALUM-LOOP-H®	LOOP HANDLE	14" x 7¼"	500	20" x 18½" x 62 ¹³ /16"	28
HAND TRUCK	ALUM-CONV®	CONVERTIBLE	18" x 7¼"	500	201/2" x 187/8" x 511/2"	40
PLATFORM TRUCK				650	20½" x 46½" x 40½"	
HAND TRUCK	ALUM-CONV-B®	CONVERTIBLE	18" x 7¼"	500	201/2" x 18 ⁷ /8" x 621/4"	40
PLATFORM TRUCK				650	201/2" x 561/2" x 447/8"	

10" x 2½" SOLID RUBBER WHEELS, model ALUM-HR **OPTIONAL STAIR GUIDES, model ALUM-SG**

Fold-Down Aluminum Hand Truck

Lightweight aluminum hand truck folds-down for storage. Telescopic upright is adjusted with spring-loaded locking mechanism. Noseplate measures 1134"W x 814"L. Dual handle design with plastic grips and knuckle guards. Rolls smoothly with two 10" diameter wheels. Wheel guards are included for use with oversize objects. Overall extended size 191/4"W x 18"L x 481/2"H. Overall size folded 19¼"W x 12"L x 33"H. Units ships fully assembled and ready to use.

MODEL NUMBER	WHEEL TYPE	UNIFORM CAPACITY (Pounds)	NET WT. (POUNDS)
DHHT-250A-FD-PN	Pneumatic	250	14
DHHT-250A-FD-UR	Red Flat-Free Urethane	250	14
DHHT-250A-FD-UB	Blue Flat-Free Urethane	250	14
DHHT-250A-FD-UY	Yellow Flat-Free Urethane	250	14
DHHT-250A-FD-UBK	Black Flat-Free Urethane	250	14

High Back Aluminum Hand Truck with Push Out

The High Back Aluminum Hand Truck with Push Out will transport tall heavy loads weighing up to 300 pounds from workstation to workstation. When the load has reached its final destination, the user simply pushes down on the back plate with their foot and the plate on the front of the unit will slide the load off. This feature reduces stress on the user's back. 8" x 1¾" semi-pneumatic wheels. Ships knockdown.

MODEL	NOSE PLATE	UNIFORM	OVERALL SIZE	NET WT.
NUMBER	(W x D)	Capacity (LBS.)	(W x D x H)	(POUNDS)
HBST-500®	13½" x 7¼"	300	18" x 17" x 55"	42

Optional Urethane Wheels for Aluminum Hand Trucks

Solid urethane foam wheels will never run flat. Offset steel hub which is great for use on hand trucks. Precision bearings with 5/8" I.D. Diameter is 10". Sawtooth tread pattern.

MODEL NUMBER	COLOR	UNIFORM CAPACITY (POUNDS)	NET WT. (POUNDS)
UFBK-10-WHL-58®	BLACK	300	4
UFRD-10-WHL-58®	RED	300	4
UFYL-10-WHL-58®	YELLOW	300	4
UFBL-10-WHL-58®	BLUE	300	4









model ALUM-CONV

48 Hours

/)to Ship



18 Hour to Sh

48 Hours

Aluminum Ergonomic Hand Truck

Heavy-duty construction, yet lightweight aluminum design, provides superior control. This unit has knuckle guard handles, fold up nose plate, and curved back plate for transporting cylindrical objects. Transporting down stairs or steep hills is no problem with this unit. 10" x 3¹/₂" pneumatic wheels are standard. Ships knockdown.

rs	MODEL	NOSE PLATE	UNIFORM	OVERALL SIZE	NET WT.
nip	NUMBER	(W x D)	CAPACITY (LBS)	(W x D x H)	(POUNDS)
	AMPC-500	11" x 11"	350	21" x 25" x 57½"	26

Four Wheel Multi-Position Steel Hand Truck

Great for uneven surfaces and outdoor work. 4" x 11/4" mold-on-rubber swivel casters are located at the back of the cart to stabilize loads and prevent tipping. The back casters will also transform the unit into a horizontal platform truck. The unit will lie back horizontally, the handle will release to a standard position, and now the cart is a platform truck. 10" x 3¹/₂" pneumatic casters. Ships knockdown.

MODEL NOSE PLATE		UNIFORM	OVERALL SIZE	NET WT.
NUMBER (W x D)		CAPACITY (LBS)	(W x D x H)	(POUNDS)
TWC-400	16¼" x 10¾"	400	23¾" x 22" x 50"	

Steel Stair Hand Truck

48 Hours

)to Ship

Unique design features tandem triple-wheel assemblies that work great when going up and down stairs. Wheel assembly smoothly rotates as you go up or down each step - eliminates the thud and bump associated with conventional two wheel hand trucks on stairs. Rear wheel assembly also allows hand truck to roll easily on 4 wheels while on flat surfaces. Single loop handle. Steel construction.

MODEL	NOSE PLATE	UNIFORM	OVERALL SIZE	NET WT.
NUMBER	(W x D)	CAPACITY (LBS)	(W x D x H)	(POUNDS)
ST-TRUCK-300	14½" x 14"	300	24" x 32" x 45¾"	38

Stair Hand Truck (Four Handles)

Quick and easy way for two people to transport a loaded hand truck up and down stairways or hills. Easy grip handles provide comfort to persons using hand truck. Removable handles conveniently store on back of hand truck when not in use. Steel construction. 10" x 3¹/₂" pneumatic wheels.

MODEL NOSE PLATE		UNIFORM	OVERALL SIZE	NET WT.
NUMBER (W x D)		CAPACITY (LBS)	(W x D x H)	(POUNDS)
HAND-TPE	13¾" x 6½"	500	21" x 17½" x 44½"	44







Appliance Carts

This cart is ideal for moving large, bulky, heavy appliances, and awkward loads. A strap and tension bar are included with this unit to hold the product in place while transporting up or down stairways, hills, or uneven surfaces.

The lightweight aluminum Appliance Cart is ideal for moving companies and delivery trucks.

model APPL-500

series APPL-1200

model APPL-500-Y

model APPL-500-A

MODEL NUMBER	DESCRIPTION	OPERATION	NOSE PLATE (W x D)	UNIFORM Capacity (LBS.)	OVERALL SIZE (W x D x H)	CASTER SIZE	STRAP Length	NET WT. (POUNDS)
APPL-500	STEEL	TURN HANDLE	24" x 3¾"	500	24" x 12" x 59½"	8" x 2½"	9.91'	47
APPL-1200-60	STEEL	RATCHET	24" x 5¼"	1,200	24" x 15" x 60"	8" x 2"*	10'	66
APPL-1200-66	STEEL	RATCHET	24" x 5¼"	1,200	24" x 15" x 66"	8" x 2"*	10'	70
APPL-1200-72	STEEL	RATCHET	24" x 5¼"	1,200	24" x 15" x 72"	8" x 2"*	10'	74
APPL-500-Y	STEEL	RATCHET	24" x 4¾"	500	24" x 12" x 60"	6" x 2"	9.83'	47
APPL-500-A	ALUMINUM	TURN HANDLE	24" x 3¾"	350	24½" x 13 x 60"	8" x 2½"	10' / 1'	34

*ALSO INCLUDES (2) 31/2" x 11/2" MOLD-ON-RUBBER SWIVEL REAR CASTERS

Dual Directional Hand Truck

The Dual Directional Hand Truck works great as a standard two-wheel hand truck or as a panel cart. This unit allows the user to transport loads forward/backward or left/right. You can transport loads of crates or boxes, or, by turning the 8" x 2" mold-on-rubber wheels, you can turn the hand truck into a panel cart. Moving down narrow aisles or doorways is no longer a problem with the adjustable wheels and easy steering. Steel construction. Painted finish.

MODEL	NOSE PLATE	OVERALL SIZE	UNIFORM	NET WT.	48 H
NUMBER	(W x D)	(W x D x H)	CAPACITY (LBS)	(POUNDS)	
DDT-500	14" x 8"	20" x 18" x 51"	600	55	Θ

File Cabinet Hand Truck

Transport file cabinets safely and easily with the File Cabinet Hand Truck. This unique design allows a single person to move file cabinets from one destination to another. The spring-loaded stabilizing arm extends 33" and the back adjusts with tension screws up to 56". This allows the operator to transport a variety cabinet sizes. Rolls on rubber wheels.

MODEL	RETRACTED SIZE	EXTENDED SIZE	UNIFORM	NET WT.
NUMBER	(W x D x H)	(W x D x H)	Capacity (LBS.)	(LBS.)
FCHT-34	19 ⁹ / ₁₆ " x 13 ¹ ⁄4" x 36 ³ ⁄4"	19 ⁹ /16" x 13 ¹ ⁄4" x 61 ³ ⁄4"	600	34

Multi-Function Luggage Cart/Chair

The Multi-Function Luggage Cart/Chair is constructed of both steel and plastic. Cart will handle lightweight uniform loads up to 65 pounds. The chair position holds up to 225 uniform pounds. This Cart/Chair is perfect for use at trade shows for transporting products, literature and small parts. (2) 3" x 3/4" hard rubber wheels are standard.

MODEL	FOLDED SIZE	SEAT SIZE	LUGGAGE	CHAIR/LUGGAGE	NET WT.
NUMBER	(W x L x H)	(W x L x H)	LIP (W x L)	UNIFORM CAP. (LBS.)	(LBS.)
LC-803	13" x 26½" x 3½"	12" x 13" x 17"	9" x 12"	225 / 65	8

High End Platform Truck

This 1,300 pound capacity truck turns conveniently on (2) 8" poly-on-steel center wheels and is stabilized by (4) 4" poly swivel casters. The combined (6) caster design and narrow platform allows the operator to maneuver through doorways and aisles. Ideal for transporting and stocking small packages in warehouses, shopping malls, grocery stores, post offices, and schools. Steel platform construction with steel uprights. Ships knockdown. Powder coat finish.

MODEL	DECK SIZE	OVERALL	UNIFORM	CASTER	NET WT.
NUMBER	(W x L)	HEIGHT	Capacity	TYPE	(LBS.)
HIGH-T	16¼" x 60"	63"	1,300	POLY-ON-STEEL	149

Panel Cart

The Panel Cart is perfect for handling items such as sheets of paneling, plywood, doors, and lumber. A convenient, removable plastic basket is included for carrying smaller items and tools. Rollers are provided on one end for easy loading and unloading. Two rigid and two swivel 4" x 2" glass-filled nylon casters are included. Ships knockdown, assembly required. Steel construction. Powder coat blue finish. Overall height is 401/2".

MODEL	DECK SIZE	UNIFORM STATIC	CASTER	CASTER	NET WT.
NUMBER	(W x L)	CAPACITY (LBS.)	SIZE	TYPE	(LBS.)
PRCT	26" x 32"	2,000	4" x 2"	GFN*	174

GLASS-FILLED NYLON

Heavy-Duty Panel Cart

You get double your money's worth with this Heavy-Duty Panel Cart. Not only is it the perfect panel cart for transporting plywood, drywall, paneling, doors, etc.; it transforms into a platform truck when you remove the 27" high support rails. This cart is powder coated blue and features a side retainer lip that keeps cargo on the deck. Two rigid and two swivel 5" x 2" poly-on-steel casters included. Ships knockdown, assembly required. Overall height is 34".

MODEL	DECK SIZE	UNIFORM STATIC	CASTER	CASTER	NET WT.
NUMBER	(W x L)	Capacity (LBS.)	Size	TYPE	(LBS.)
PRCT-HD	29½" x 36"	4,000	5" x 2"	POLY-ON-STEEL	247



Ne



POWDER





DESIGN





Vertical Panel Cart

Heavy duty steel platform cart supports multiple sizes of sheet material such as paneling, plywood, drywall or anything that is long, bulky and hard to handle. Ideal for lumberyards and hardware stores. Rolls on (4) 6" x 2" swivel poly-on-poly and (2) 8" x 2" rigid poly-on-poly casters. Center caster provides great maneuverability.

MODEL	OVERALL SIZE	UNIFORM STATIC	CASTER	CASTER	NET WT.
NUMBER	(W x L x H)	Capacity (LBS.)	SIZE	Type	(LBS.)
PANEL-V	30" x 48" x 47"	2,000	(4) 6" & (2) 8"	POLY	150

Drywall & Panel Cart

Versatile cart for moving drywall, wood and other types of panel products. Maximum usable panel height is 60". Portable on two rigid and two swivel casters. Welded steel construction with painted finish. Knock-down design for lower shipping costs.

MODEL NUMBER	OVERALL SIZE (W x L x H)	UNIFORM STATIC Capacity (LBS.)	CASTER SIZE	CASTER Type	NET WT. (LBS.)
PRCT-S-MR	23" x 48" x 48"	3,000	2" x 8"	RUBBER	89
PRCT-S-GN	23" x 48" x 48"	3,000	2" x 8"	GFN*	90
*GLASS FILLED NYLO	N				

Nestable Panel Cart

Unique design saves valuable space when stored. Overall size of each cart is 721/2"W x 321/2"D x 391/2"H. Each additional cart only requires an additional 10¹/₂" of space. Features front storage area for handling paneling and sheet goods. Rear shelf is ideal for storing smaller products. Each unit includes (4) 5" x 11/4" poly-on-poly swivel casters; one with a total locking brake. Welded steel construction. Powder coat blue finish.



MODEL	OVERALL SIZE	UNIFORM STATIC	CASTER	CASTER	NET WT.
NUMBER	(W x D)	Capacity (LBS.)	Size	Type	(LBS.)
PRCT-N	72½" x 32½"	2,000	5" x 1¼"	POLY-ON-POLY	175

Low Platform Panel Carts

All purpose large flat panel cart is constructed of steel. Features removable uprights and an easy-roll entry roller on one end. Carts roll smoothly on (2) rigid and (2) swivel 8" x 2" phenolic casters with side brakes. Durable powder coat finish.

MODEL NUMBER	DECK SIZE (W x L)	UNIFORM STATIC CAPACITY (LBS.)	PLATFORM HEIGHT	NET WT. (LBS.)
DWC-EL-36	12" x 39½"	2,000	5"	202
DWC-EL-48	12" x 51½"	2,000	5"	233
DWC-EL-60	12" x 64"	2,000	5"	250
DWC-EL-72	12" x 75½"	2,000	5"	270

Horizontal Panel Cart

This two tier cart is great for handling panels and small items. The top deck is 30" high while the bottom deck is 8" off the ground. Four sliding posts can be locked in the up position to prevent products from sliding. Rolls on (4) 2" x 6" swivel and (2) 2" x 8" rigid polyolfin casters. Center caster provides great maneuverability.

er opp					
	MODEL	OVERALL BASE	OVERALL TOP	UNIFORM STATIC	NET WT.
	NUMBER	(WxLxH)	(W x L x H)	CAPACITY (LBS.)	(LBS.)
WDER	PANEL-H®	29" x 42" x 10¾"	29" x 64" x 30½"	2,000	125

Panel Truck with Storage Tray

Heavy-duty panel truck with built-in storage tray for use with steel and panel goods. Great for use in home centers, warehouses and similar locations. Deck opening will hold panels up to 11" thick. Steel deck includes a 2" high lip for holding steel goods. Overall height is 46" while the deck height is 11". Steel construction with powder coat blue finish.

MODEL NUMBER	PLATFORM Size (L x W)	UNIFORM STATIC Capacity (LBS.)	CASTER TYPE	NET WT. (LBS.)
PRCT-T-2448-MR	24" x 48"	1,000	MOLD-ON-RUBBER	155
PRCT-T-2448-PU	24" x 48"	1,500	POLY-ON-STEEL	165
PRCT-T-3060-MR	30" x 60"	1,000	MOLD-ON-RUBBER	220
PRCT-T-3060-PU	30" x 60"	1,500	POLY-ON-STEEL	230

Easy Move Panel Cart

The High Handle Panel Cart is ergonomically designed for quickly and easily moving sheets of plywood or drywall down small aisles or through doorways. To prevent tipping, rollers have been added to the front and back of the unit for support. Includes (2) 10" x $2\frac{1}{2}$ " solid rubber and (2) 3" steel wheels standard. Sloped platform is 21" x $8\frac{1}{2}$ ".

MODEL	UNIFORM STATIC		NET WT.
NUMBER	CAPACITY (LBS.)	CASTER SIZE	(LBS.)
HT-PANEL	750	(2)10" x 2½" & (2) 3"	72

Lightweight Door & Panel Dolly

Lightweight door and panel dolly with auto-clamp feature. Unique design grips plate/slab when weight is added. Opening for use with maximum 2¼" thick plate/slab. Several different types of wheels to choose from. Steel construction with painted blue finish.

MODEL	UNIFORM STATIC	CASTER	CASTER	NET WT.
NUMBER	CAPACITY (LBS.)	SIZE	TYPE	(LBS.)
PLDL-LD-2-4PP	350	4"	POLY-ON-POLY	9

Heavy-Duty Plate/Slab Dolly

Heavy-duty plate/slab dolly with auto-clamp feature. Unique design grips plate/slab when weight is added. Opening for use with maximum 4" thick plate/slab. Hand holds are great for carrying. Strap (not included) can also be hooked to hand holds. Several different types to choose from. Steel construction with padded inside.

MODEL NUMBER	UNIFORM STATIC Capacity (LBS.)	WHEEL SIZE	CASTER TYPE	NET WT. (LBS.)
PLDL-HD-4-8MR	1,200	8"	RUBBER-ON-STEEL	32
PLDL-HD-4-8PS	1,500	8"	POLY-ON-STEEL	32
PLDL-HD-4-8GFN	1,500	8"	GLASS-FILLED NYLON	30
PLDL-HD-4-10PN	750	10"	PNEUMATIC	26
PLDL-HD-4-10FF	500	10"	FOAM-FILLED	26

A-Frame Carts

If you need to move bulky sheets of material such as drywall, plywood, paneling, or sheets of metal, you need the heavy-duty A-Frame Cart. A convenient parts tray is included between the A-frame uprights. Unit is easily secured for loading and unloading by using the foot operated caster lock. Includes two rigid and two swivel casters. All steel construction with a durable powder coat finish. Ships knockdown, assembly required.

MODEL NUMBER	DECK SIZE (W x L)	UNIFORM STATIC Capacity (LBS.)	CASTER SIZE	CASTER TYPE	NET WT. (LBS.)
AF-2436	24" x 36"	2,000	5" x 2"	POLY-ON-STEEL	195
AF-2448	24" x 48"	2,000	5" x 2"	POLY-ON-STEEL	215
AF-3048	30" x 48"	2,000	5" x 2"	POLY-ON-STEEL	230
AF-3060	30" x 60"	2,000	5" x 2"	POLY-ON-STEEL	258
AF-3672	36" x 72"	2,000	5" x 2"	POLY-ON-STEEL	287

A-Frame Storage Cart

The portable A-Frame Cart with storage rack is ideal for storage and transporting pipe, conduit and other types of bar material. Storage arms extend 12" beyond frame with a clearance of 7¼" between arms. Unit rolls on (2) rigid and (2) swivel 5" poly-on-steel casters. Base is powder coat blue while the storage rack is zinc plated.

MODEL NUMBER	OVERALL SIZE (W x L x H)	UNIFORM STATIC CAPACITY (LBS.)	CASTERS	NET WT. (POUNDS)	
AFSR-3672	36" x 72" x 66"	2,000	POLY-ON-STEEL	360	

Platform Cart with Versatile Dividers

These innovative units are perfect for transporting a large array of products throughout your warehouse. The removable handles can be configured in a way to optimize space and convenience. Each unit includes (5) sets of removable handles. Units roll smoothly on (4) 5" x 2" swivel phenolic and (2) 5" x 2" rigid phenolic casters. Casters are mounted in "tilt" configuration for easy in-place turning.

MODEL NUMBER	OVERALL SIZE (W x L x H)	UNIFORM STATIC CAPACITY (LBS.)	WHEELS	NET WT. (LBS.)
VERSA-3060	30" x 60¼" x 9"	3,000	5" x 2"	250
VERSA-3672	36" x 72¼" x 9"	3,000	5" x 2"	360







OATED





POWDER

48 Hours











()to Ship

Multi-Tier Stock Carts

to baskets. Ideal for stocking parts in work stations. Casters allow the parts to be moved to wherever they are needed. Shelves will tilt between 0° and 45°. Shelf angle is locked with a hand operated friction lock screw. Bottom shelf includes a 2" high lip on all four sides. Middle and top shelves include a 11/2"H lip on all four sides. Bottom shelf height is 51/2". Middle shelf height is 33". Top shelf height is 56¼". Overall cart size (not including baskets) is 18¼"W x 27¹/₂"L x 60"H (35"H for two-shelf models). Rolls smoothly on two rigid and two swivel 4" x 2" casters. Steel construction. Powder coat finish.

This unique cart makes it easy to organize and reach parts. Tilting shelves allow easy access

MODEL NUMBER	SHELF SIZE (W x L)	UNIFORM STATIC Capacity (LBS.)	BASKET SIZES (W x L x H)	NET WEIGHT (POUNDS)
TSCT-2	16" x 24"	200	NONE	98
TSCT-3	16" x 24"	200	NONE	132
TSCT-2B	16" x 24"	200	(1) 15½" x 23½" x 16½" (1) 15½" x 23½" x 12½"	114
ТЅСТ-3В	16" x 24"	300	(1) 15½" x 23½" x 16½" (1) 15½" x 23½" x 12½" (2) 11½" x 15½" x 8½"	150
ADDITIONAL PLA	STIC BINS			
TSCT-LGB		15½"W x 23½	"L x 16½"H	9
TSCT-MDB	15½"W x 23½"L x 12½"H			7
TSCT-SMB		11½"W x 15½	"L x 8½"H	3

Folding Security Trucks

This portable cart is designed to safely hold your valuable equipment. All welded components and wire mesh walls combine to make this truck extremely tough and strong. Center shelf folds down to create (2) 32¹/₂"H areas or remains in the up position to provide full 66¹/₂"H area of storage. Special door locking latch and padlock clasp (padlock not included) for securing stored contents. Rolls on 6" x 2" molded-on rubber casters, 2 rigid and 2 swivel swivel. The overall size is 27"W x 44"L x 761/2"H. The usable size with shelf down is 241/2"D x 421/2"W x 321/2"H and with the shelf up 24"D x 411/2"W x 661/2"H. Unit will fold down to 51"D x 76"W x 12"H for storage or transport.

MODEL	OVERALL SIZE	UNIFORM STATIC	FINISH	NET WT.
NUMBER	(W x D x H)	Capacity (LBS.)		(POUNDS)
FST-2744-2	44" x 27" x 76½"	2,000	PAINTED GREY	240





ROL-3143-2

2nd shelf

t fold

ROL-3143-1



Foldable/Nestable Roller Containers

Provides convenient portability between work cells or for delivery or distribution of goods. All welded steel construction. Units roll smoothly on casters. To figure individual uniform shelf capacity divide the number of shelves by total capacity.



ROL-55

	HOL-00	ROL-85		10L-33		120
MODEL NUMBER	NUMBER OF Shelves	OVERALL SIZE (W x D x H)	MESH OPENINGS	TOTAL UNIFORM Capacity	CASTERS	NET WT. (LBS.)
BLUE PAINTED FI	NISH					
ROL-1834-3	3	34" x 18" x 59"	3¼" x 11"	990 lbs.	11/2" x 5" (4) swivel w/brakes	70
ROL-3143-2	2	40" x 28" x 68"	13 ³ /8" x 6 ¹ /4"	1,100 lbs.	11/4" x 5" (2) swivel w/brakes & (2) rigid	160
ROL-3143-1	1	43¼" x 31¾" x 66¾"	13 ³ /8" x 6 ¹ /4"	880 lbs.	11/4" x 5" (2) swivel w/brakes & (2) rigid	125
GALVANIZED FINI	SH					
ROL-55	1	26 ¹ /4" x 23 ³ /8" x 35 ⁵ /8"	2" x 1 ⁷ /8"	660 lbs.	11/4" x 5" (2) swivel w/brakes & (2) rigid	55
ROL-80	1	28¼" x 31½" x 66"	12½" x 4"	660 lbs.	11/2" x 5" (2) swivel w/brakes & (2) rigid	80
ROL-85	2	27½" x 32" x 68¼"	18½" x 4½"	660 lbs.	11/4" x 5" (2) swivel w/brakes & (2) rigid	84
ROL-95	1	26 ³ /8" x 32" x 59"	15¾" x 3¾"	660 lbs.	11/2" x 5" (2) swivel w/brakes & (2) rigid	94
ROL-185	1	43½" x 30" x 69"	21/2" x 11/2"	660 lbs.	11/2" x 6" (2) swivel w/brakes & (2) rigid	185
ROL-120	1	24" x 32¼" x 66"	1¾" x 1¾"	880 lbs.	1¾" x 5" (2) swivel w/brakes & (2) rigid	117



Portable Carpet Dolly & Dispenser

Portable Carpet Dollies allows for easy movement of long and heavy rolls of carpeting. V-groove platform holds carpet rolls securely in place.

Carpet Dispenser minimize lifting and pulling. Slide carpet onto rollers. Carpet unrolls as needed. Retractable legs stabilize cart.

Each unit includes two 16" diameter by 4" wide wheels. Uniform capacity 500 lbs. Welded steel construction with powder coat blue finish.

MODEL NUMBER	OVERALL SIZE (W x L x H)	PLATFORM Size (W x L)	WHEEL STYLE	NET WT. (LBS.)
CARPET-45	26" x 60" x 20"	16" x 60"	FULLY PNEUMATIC	45
CARPET-45-FF	26" x 60" x 20"	16" x 60"	FOAM-FILLED	45
CARPET-D	26" x 60" x 20"	16" x 60"	FULLY PNEUMATIC	95
CARPET-D-FF	26" x 60" x 20"	16" x 60"	FOAM-FILLED	95

Gas Powered Trailer Mover

Gas Power Trailer Mover is compact in size and easy to use. They are highly maneuverable, making them ideal for turning in tight spaces (not recommended for use on an incline or slope). Six horsepower gasoline engine combined with a hydrostatic transmission provides variable speed control and generous low speed torque for precise positioning. Rugged front foam filled tires with aggressive tread pattern provide service on unpaved surfaces. Engine powered lift eliminates hand jacking. Three size ball hitch quickly converts to common sizes. Ball sizes; 1%, 2" and $2^{5}/16$ ". Overall size with handle up is 51"W x 66"L x 40"H.

MODEL	BALL	UNIFORM PULL	UNIFORM TONGUE	NET WT.
NUMBER	Service	Capacity	LIFT CAPACITY	(LBS.)
PTM-GPT	17" to 27"	12,000 lbs.	1,000 lbs.	600

Power Move Masters 24V DC POWERED STANDARD

Power Move Masters are compact in size and easy to use. They are highly maneuverable, making them ideal for turning in tight spaces (not recommended for use on an incline or slope). DC powered for smooth, quiet operation with variable speed control for generous low speed torque and precise positioning. Built in battery charger for quick recovery. Most models feature robust hydraulics to ensure superb push or pull traction. In addition, their ergonomic design provides stability and simple control. A variety of hitch attachments along with other options are available, contact factory. The tire size is 9½" x 18". The hydraulic lift is standard on models PMM-3000 and PMM-3000-15, 9" to 29". Optional hydraulic lift option available on model PMM-700 and PMM-1000. Three point mounting configurations allow for adjustable service range.

MODEL NUMBER	OVERALL SIZE (W x L x H)	UNIFORM Tongue-Weight Load From Lift (Lbs.)	UNIFORM MAXIMUM PULL WEIGHT (LBS.)	NET WT. (LBS.)
PMM-1000	38" x 53" x 38"	1,000	12,000	595
PMM-3000	36" x 78" x 43"	3,000	40,000	1550
PMM-3000-15	36" x 96" x 43"	3,000/1,500*	40,000	2150
PMM-HYD-LIFT	HYDRAULIC LIFT OPTION, 9" TO 26" ADJUSTABLE			

*3,000 lbs. CENTER / 1,500 lbs. FRONT LIFT

Traction-Drive Carts DC POWERED STANDARD

Unique carts feature built-in traction-drive system for easy transportability. Ideal for applications including mail rooms, hospitals, supermarkets, hotels and warehouses. Features 450W electric drive motor with two 70Ah batteries for power. 110V AC internal battery charger is included. Variable throttle speed control for precise maneuvering and positioning is located in the handle. Units roll smoothly on (2) 8" rubber front wheels and (2) 10" pneumatic rear wheels. Walking speed is 0-3.7 mph when unloaded and 0-2.5 mph when loaded. Speed control is conveniently located in handle. Handle pivots back towards operator and includes horn and emergency stop. Maximum incline is 7 degrees. Each shelf includes a non-slip rubber top surface. Includes on-board charger.

MODEL NUMBER	DECK SIZE (W x L x H)	SHELF HEIGHT	UNIFORM BOTTOM Shelf Capacity	UNIFORM TOP Shelf Capacity	NET WT. (LBS.)
E-CART	26" x 46" x 14½"	13¾"	500 lbs.		338
E-CART-2	26" x 46" x 41"	13¾" / 41"	500 lbs.	220 lbs.	364



model PMM-3000-15

model PMM-3000







48 Hours



MADE IN THE USA



Powered Platform Truck DC POWERED STANDARD

High quality battery-powered truck ideal for transporting all sorts of loads in warehouses, hospitals and factories. Red throttle controls infinite speed in forward or reverse, and unit stops when throttle is released. Emergency reverse belly switch; when actuated, instantly reverses direction and moves the unit forward away from the operator until the switch is released. Stable 4 wheel platform. Two 10" pneumatic tires and two 5" poly on steel swivel wheels provide a high degree of maneuverability. Features an anti-slip rugged deck surface. Maximum speed is 1.8 mph loaded and 2.3 mph unloaded. This truck comes with 2, 12V, 40Ah maintenance free batteries, 70A Curtis controller, 370W drive motor, integral battery charger, and battery level gauge. 3-4 hour operation at full charge - 6 hours when used intermittently. Battery recharge time is 8-8.5 hours.

MODEL	DECK SIZE	DECK	OVERALL SIZE	UNIFORM STATIC	NET WT.
NUMBER	(W x L)	HEIGHT	(W x L x H)	Capacity (LBS.)	(LBS.)
VPPT	36" x 43"	12 ³ /8"	36¼" x 50" x 42½	1,000	245

Electric Material Handling Cart DC POWERED STANDARD

Transport a large array of products throughout your warehouse efficiently with this motorized cart. Features a heavy duty 650 watt motor, (2) 50 amp batteries, 5 amp-hour on-board battery charger, LED battery level gauge, horn/power kill button, intelligent electronic braking, variable speed dial, and a Penny & Giles motor controller. Unit operates smoothly with fingertip forward and reverse levers and 10" foam filled drive tires. Pinpoint turning is accurate with the mid axle drive feature. Maximum speed is 4.8 mph.

MODEL	DECK SIZE	DECK	UNIFORM STATIC	NET WT.
NUMBER	(W x L)	HEIGHT	Capacity (LBS.)	(LBS.)
EMHC-2460	24" x 60"	11²/3"	1,100	320

Off-Road Traction Drive Powered Cart 24V DC POWERED STANDARD

Ideal on the farm or in the factory. Features a robust 24V DC 600 watt drive motor, (2) 12 volt batteries with charger and level gauge, low/high speed, LED headlights, wire storage, basket, and forward/reverse. Low speed is $1\frac{1}{2}$ m.p.h. High speed is $1\frac{7}{8}$ m.p.h. (reverse is $1\frac{1}{2}$ m.p.h.). Unit runs for approximately 4 hours before it needs charged. Climb a 13° incline easily with 400 lbs. capacity or less. Side guards are removable. Overall size $33\frac{1}{2}$ "W x 72"L x $37\frac{3}{4}$ "H.

MODEL	DECK SIZE	UNIFORM STATIC	WHEEL SIZE	NET WT.
NUMBER	(W x L x H)	Capacity (LBS.)		(LBS.)
OROAD-400	31½" x 52½" x 15¾"	500 rough 600 smooth	3½" x 11" rear 6" x 14" front	323

Industrial Bicycles

A quick, easy and safe way to move around large facilities. Built with rider friendly features and the ability to handle various loads while moving through a facility with ease and efficiency. A three wheel design includes hand brakes for sure stopping. Adjustable height seat for different sized people. Large payload / cargo area included. Additional options available, contact factory.

MODEL	OVERALL SIZE	UNIFORM STATIC		NET WT.
NUMBER	(W x L x H)	CAPACITY (LBS.)	COLORS	(LBS.)
IBIKE-3-DC-R	29" x 70" x 43"	250	RED	65
IBIKE-3-DC-B	29" x 70" x 43"	250	BLUE	65
IBIKE-3-DC-G	29" x 70" x 43"	250	GREEN	65
IBIKE-3-DC-P	29" x 70" x 43"	250	PURPLE	65
IBIKE-3-DCHH-Y	29" x 70" x 43"	350	YELLOW	81
IBIKE-3-HH-Y	33½" x 79" x 45"	500	YELLOW	106
IBIKE-3-HH-BL	33½" x 79" x 45"	500	BLACK	106

Manual Scooter with Brake

Get where you need to be quickly and safely with our manually powered Scooter. Sturdy foot rest includes a manually operated rear brake that safely stops the Scooter at your destination. Fixed height handle bars control front wheel maneuvering through narrow aisles and doorways. A 14" long x 18" wide front platform holds up to 55 uniform pounds, ideal for crates, boxes, and other small loads. Rolls on high performance 3" polyurethane wheels. Ships knockdown. Optional bolt-on basket available separately. Capacity of the basket is 15 pounds.

MODEL NUMBER	OVERALL SIZE (W x L)	PLATFORM Size (W x L)	UNIFORM STATIC Capacity (LBS.)	NET WT. (LBS.)
SCOOT-500	18" x 36"	18" x 14"	250	30
SCOOT-BSK	OPTIONAL BOLT-ON WIRE BASKET			4

INDUSTRIAL CARTS & DOLLIES

Aluminum Pallet Dollies

Designed to transport pallets with ease. All welded aluminum construction is durable yet lightweight. Features heavy-duty 3" wide x 31/2" diameter phenolic rollers for easy portability. Choose from either tilt or non-tilt styles. Tilt style allows for easier turning than non-tilt style. Optional loops/handle and a center support crossbar are available. Dolly height is 41/4".

MODEL NUMBER	OVERALL SIZE (W x L)	UNIFORM STATIC Capacity (LBS.)	NUMBER OF Rollers	DECK HEIGHT	NET WT. (LBS.)
DOL-3636-6NT	36" x 36"	4,000	6	NON-TILT	38 UPS
DOL-3642-6NT	36" x 42"	4,000	6	NON-TILT	41 UPS
DOL-3648-6NT	36" x 48"	4,000	6	NON-TILT	42 UPS
DOL-4048-6NT	40" x 48"	4,000	6	NON-TILT	43
DOL-4242-6NT	42" x 42"	4,000	6	NON-TILT	44
DOL-4248-6NT	42" x 48"	4,000	6	NON-TILT	44
DOL-4848-6NT	48" x 48"	4,000	6	NON-TILT	46
DOL-4848-8NT	48" x 48"	6,000	8	NON-TILT	50
DOL-4848-10NT	48" x 48"	8,000	10	NON-TILT	50
DOL-3636-6T	36" x 36"	4,000	6	TILT	38 UPS
DOL-3642-6T	36" x 42"	4,000	6	TILT	41 UPS
DOL-3648-6T	36" x 48"	4,000	6	TILT	42 UPS
DOL-4048-6T	40" x 48"	4,000	6	TILT	43
DOL-4242-6T	42" x 42"	4,000	6	TILT	44
DOL-4248-6T	42" x 48"	4,000	6	TILT	44
DOL-4848-6T	48" x 48"	4,000	6	TILT	45
DOL-3636-8T	36" x 36"	6,000	8	TILT	44 UPS
DOL-3642-8T	36" x 42"	6,000	8	TILT	48 UPS
DOL-3648-8T®	36" x 48"	6,000	8	TILT	49 UPS
DOL-4048-8T®	40" x 48"	6,000	8	TILT	50
DOL-4242-8T	42" x 42"	6,000	8	TILT	52
DOL-4848-8T®	48" x 48"	6,000	8	TILT	53
DOL-3636-10T	36" x 36"	8,000	10	TILT	48 UPS
DOL-3642-10T	36" x 42"	8,000	10	TILT	52 UPS
DOL-3648-10T	36" x 48"	8,000	10	TILT	53 UPS
DOL-4048-10T	40" x 48"	8,000	10	TILT	54
DOL-4242-10T	42" x 42"	8,000	10	TILT	55
DOL-4848-10T	48" x 48"	8,000	10	TILT	56
OPTIONS					
DOL-FL-LK	FLOOR LOCK	(FACTORY INSTALLED)			8
DOL-HDL	LOOPS AND H				3
DOL-CB	CENTER SUPF	PORT CROSS BAR	(FACTORY INSTAL	LED)	10





Loops and Handle work great for pulling. Includes one loop at each end of dolly and one handle. Factory installed. Model DOL-HDL

A center support crossbar is available as an extra support on smaller loads Factory installed. Model DOL-CB.

Aluminum Channel Dollies

These versatile dollies are manufactured from aluminum for a strong yet lightweight design. Aluminum construction will not rust and never needs painting. Each dolly includes four swivel casters for maximum maneuverability. Order with optional Pull Strap or Hook for added operator convenience - see page 223.

MODEL NUMBER	OVERALL SIZE (W x L)	UNIFORM Capacity	DECK Height	CASTER Size	CASTER Type	NET WT. (LBS.)	LIST PRICE Each
ACP-1824-9	18" x 24"	900	6"	3" x 1¼"	HARD RUBBER	14	\$119.00
ACP-2130-9	21" x 30"	900	6"	3" x 1¼"	HARD RUBBER	16	123.00
ACP-2136-20	21" x 36"	2,000	10 ⁵ /8"	5" x 2"	POLY-ON-STEEL	43	\$249.00
ACP-2436-20	24" x 36"	2,000	10 ⁵ /8"	5" x 2"	POLY-ON-STEEL	45	252.00
ACP-2442-20	24" x 42"	2,000	10 ⁵ /8"	5" x 2"	POLY-ON-STEEL	47	262.00
ACP-4042-20	40" x 42"	2,000	10 ⁵ /8"	5" x 2"	POLY-ON-STEEL	53	293.00
						DC-2	20/UPS/FC-100



2.000 LBS CAPACITY UNITS



Cast Aluminum Dollies

These Aluminum Dollies are easy to use and provide efficient moving time. Box-like frames have integral sides and deeply fluted tops. Dollies include 31/2" diameter x 3" wide phenolic rollers. They are excellent for moving heavy crates and machinery. Note: Except when used individually, corners should be turned by lifting the load and rotating each dolly individually. Overall height 41/4".

MODEL NUMBER	DECK SIZE (W x L)	UNIFORM STATIC Capacity (LBS.)	NUMBER OF ROLLERS	NET WT. Pounds	LIST PRICE EACH
VPRDO-1	4½" x 4½"	1,500	1	5	\$46.00
VPRDO-2	4¾" x 8½"	3,000	2	8	65.00
VPRDO-4	8½" x 8½"	6,000	4	13	77.00
VPRDO-6	8½" x 12½"	9,000	6	20	149.00
VPRDO-6T	8½" x 12½"	3,000	6	20	149.00
SUFFIX "6T" IS A TII	UFFIX "6T" IS A TILTING DESIGN				

series VPLDO/A



optional brakes.











Aluminum and Steel Plate Dollies

Plate Dollies are manufactured with a ³/₈" thick raised diamond pattern aluminum or steel tread plate. A smooth deck is available upon request. Dollies are approximately 6" high and include 4" x 2" mold-on-rubber casters, 2 rigid and 2 swivel with brake. Casters are bolted onto the aluminum dollies and welded onto the steel dollies. Optional pull strap (for aluminum dollies) or hook is available separately.

MODEL NUMBER	DECK SIZE (W x L)	UNIFORM STATIC Capacity (LBS.)	CASTER SIZE	DECK HEIGHT	NET WT. (LBS.)
ALUMINUM PLATE DOL	LIES				
VPLDO/A-1418	14" x 18"	1,200	4" x 2"	6"	31
VPLDO/A-1824	18" x 24"	1,200	4" x 2"	6"	40
VPLDO/A-2430	24" x 30"	1,200	4" x 2"	6"	52
STEEL PLATE DOLLIES					
VPLDO/S-1418	14" x 18"	1,200	4" x 2"	6"	58
VPLDO/S-1824	18" x 24"	1,200	4" x 2"	6"	80
VPLDO/S-2430	24" x 30"	1,200	4" x 2"	6"	130

OPTIONAL (4) SWIVEL CASTER WITH LOCKS, MODEL VPLDO/S-AS

Adjustable Tote Dollies

Unique design is adjustable in both width and length for use with different size totes. Easy to adjust by loosening the screws and sliding each side in or out. Each unit includes four swivel casters (one with brake) that are attached with caster pads. Overall size is 3" greater than the usable size. Welded steel construction for maximum strength with powder coat blue finish. Totes sold separately.

MODEL NUMBER	MINIMUM Usable size	MAXIMUM USABLE SIZE	UNIFORM STATIC Capacity (LBS.)	CASTER Size / Style	NET WT. (LBS.)
ATD-1622-4	16"W x 22"L	24"W x 34"L	2,000	4" GFN*	38
ATD-1622-6	16"W x 22"L	24"W x 34"L	3,000	6" GFN*	42
*GLASS-FILLED NYL	ON				

Steel Pro-Movers

Move pallets without a fork truck or pallet jack. Designed for holding standard wooden pallets. Transport pallets and skids with these open frame all welded steel dollies. 2,000 lb. capacity units roll smoothly on four swivel mold-on-rubber casters. 4,000 lb. capacity units feature glass-filled-nylon swivel casters. Casters are bolted to each dolly. Blue powder coat finish.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC Capacity (LBS.)	CASTER SIZE	NET WT. (LBS.)
PRM-4048	40" x 48"	87/8"	2,000	6" x 2"	71
PRM-4248	42" x 48"	8 ⁷ /8"	2,000	6" x 2"	85
PRM-4848	48" x 48"	87/8"	2,000	6" x 2"	95
PRM-4048-8	40" x 48"	11"	4,000	8" x 2"	71
PRM-4248-8	42" x 48"	11"	4,000	8" x 2"	85
PRM-4848-8	48" x 48"	11"	4,000	8" x 2"	95

Lo-Profile Floor Hugger Dolly

This lo-profile steel dolly allows for loading and unloading of materials at floor level. The (4) $3" \ge 14$ " hard rubber swivel casters allow for easy portability. The handles allow for convenient positioning and transporting. The overall height is 43%".

MODEL	OVERALL SIZE	USABLE SIZE	UNIFORM STATIC	NET WT.
NUMBER	(W x L x H)	(W x L x H)	CAPACITY (LBS.)	(LBS.)
LFH-55®	31" x 22" x 4 ³ /8"	21" x 21½" x 2"	840	66

Nose Plate Dollies

These lever action dollies are excellent for moving file cabinets, appliances, drums, crates and cartons. Heavy-duty steel dolly is designed to be counterbalanced so you do not need to lift the entire weight of the load. Simply tilt the load and slide dolly under. Complete product is vinyl covered to help eliminate scrapes and scratches. Equipped with hard rubber wheels (2) $3" \ge 1\frac{1}{2}"$ axle mounted and (2) $2\frac{1}{2}" \ge 1\frac{1}{4}"$ swivel casters.

MODEL NUMBER	DECK SIZE (W x L)	DECK Height	UNIFORM STATIC Capacity (LBS.)	NET WT. (LBS.)
NPL-21®	15" x 32"	4"	600	25
NPL-24®	18" x 32"	4"	600	29

INDUSTRIAL GARTS & DOLL

Hardwood Dollies

Open Deck, Solid Deck, Vinyl Covered, Carpet End, Rubber End

Transport boxes, crates, or supplies with these rugged dollies. Units maneuver on four swivel hard rubber casters. Assembly required. Optional Pull Strap or Hook available.

HARDWOOD DOLLY ACCESSORIES

MODEL		NET WT.					
NUMBER	DESCRIPTION	(LBS.)					
STRAP-8	4 FOOT LONG NYLON LOOP PULL STRAP	1					
HOOK-8	4 FOOT LONG METAL HOOK	3					
HARDWOOD DOLLIES	HARDWOOD DOLLIES SOLD SEPARATELY						

OPEN DECK HARDWOOD DOLLIES

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC Capacity (LBS.)	CASTER SIZE	NET WT. (LBS.)
HDOF-1624-9	16" x 24"	5 ½"	900	3" x 1¼"	19
HDOF-2436-9	24" x 36"	5 ½"	900	3" x 1¼"	24
HDOF-1624-12	16" x 24"	6¾"	1,200	4" x 1¼"	20
HDOF-2436-12	24" x 36"	6¾"	1,200	4" x 1¼"	26

SOLID DECK HARDWOOD DOLLIES

MODEL	DECK SIZE	DECK	UNIFORM STATIC	CASTER	NET WT.
NUMBER	(W x L)	HEIGHT	CAPACITY (LBS.)	SIZE	(LBS.)
HDOS-1624-9	16" x 24"	51⁄2"	900	3" x 1¼"	24
HDOS-2436-9	24" x 36"	5 ½"	900	3" x 1¼"	35
HDOS-1624-12	16" x 24"	6¾"	1,200	4" x 1¼"	31
HDOS-2436-12	24" x 36"	6¾"	1,200	4" x 1¼"	42

VINYL COVERED HARDWOOD DOLLIES

MODEL	DECK SIZE	DECK	UNIFORM STATIC	CASTER	NET WT.
NUMBER	(W x L)	HEIGHT	CAPACITY (LBS.)	SIZE	(LBS.)
FDOL-1624-9	16" x 24"	5¾"	900	3" x 1¼"	20
FDOL-2436-9	24" x 36"	5 ³ ⁄4"	900	3" x 1¼"	30
FDOL-1624-12	16" x 24"	7"	1,200	4" x 1¼"	23
FDOL-2436-12	24" x 36"	7"	1,200	4" x 1¼"	34
FDOL-2448-12	24" x 48"	7"	1,200	4" x 1¼"	41

RUBBER END HARDWOOD DOLLY

MODEL	DECK SIZE	DECK	UNIFORM STATIC	CASTER	NET WT.
NUMBER	(W x L)	HEIGHT	Capacity (LBS.)	SIZE	(LBS.)
HDOR-1830-12	18" x 30"	7"	1,200	4" x 1¼"	20

CARPET HARDWOOD DOLLIES

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC Capacity (LBS.)	CASTER SIZE	NET WT. (LBS.)
HDOC-1624-9	16" x 24"	5¾"	900	3" x 1¼"	22
HDOC-1830-9®	18" x 30"	5 ¾"	900	3" x 1¼"	29
HDOSC-1624-12	16" x 24"	6¾"	1,200	4" x 1¼"	34
HDOSC-2436-12	24" x 36"	6¾"	1,200	4" x 1¼"	48

Dolly Converter

Black handles loads up to 250 pounds. Sold in pairs, not pre-drilled. No hardware included.

MODEL NUMBER	WIDTH	HEIGHT	UNIFORM STATIC Capacity (LBS.)	NET WT. (LBS.)
D-CNVR-250	12"	37"	250	26

Fiberwood Dollies

Fiberwood construction dollies feature a rubber padded surface and two hand holes to carry the unit. The PVC edge strip protects walls from scrapes. Units roll on four swivel wheels which are non-marring and oil-resistant.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC Capacity (LBS.)	CASTER Size / Type	NET WT. (LBS.)
FWD-1824-3R	18" x 24"	5"	800	3" RUBBER	16
FWD-1836-3R	18" x 36"	5"	700	3" RUBBER	18
FWD-2436-3R	24" x 36"	5"	600	3" RUBBER	21
FWD-2436-4PP	24" x 36"	51⁄2"	600	4" PP*	22
*POLYPROPYLENE CAST	ERS				



model D-CNVR-250

series FWD

48 Hours

223

GENERAL DUTY ALL WEATHER



model VPJ-DOL

PADDED

model DOL-1830-P

model KNEE-D

model PDH-1624

model LEG-D

Hours to Ship

New≤

QPC-7280-DP

→)to Ship

model VPJ-9

48 Hours)to Ship

QPC-7280-VP



QPC-7280-UP

Quilted Moving Pads

Cushion and protect furniture, machinery, and electronic equipment. Each pad measures 72" wide by 80" long. Units are sold a dozen at a time. Model QPC-7280-UP is water and mildew resistant.

MODEL NUMBER	DESCRIPTION	NET WEIGHT (POUNDS)
QPC-7280-DP	GENERAL DUTY (both sides cotton)	64
QPC-7280-UP	ALL WEATHER (both sides polyester)	82
QPC-7280-VP	HEAVY-DUTY (one side polyester/other side cotton)	79

Auto Dollies

Move cars in any direction with our Auto Dollies. Each dolly rolls on four swivel rubber casters. The height is 2⁵/₈" to bottom of v-channel. Steel construction with painted finish.

MODEL	DECK SIZE	UNIFORM STATIC CAPACITY	WHEEL	NET WT. PER
NUMBER	(W x L)	(LBS.) PER SET	SIZE	SET (LBS.)
ADOL-1216-6K®	12" x 16"	6,000	3" x 1 ⁷ /8"	78

Hydraulic Vehicle Positioning Jacks

Great product used for effortless lifting and moving of vehicles. Simply slide product around bottom half of tire then pump foot pedal. Product will squeeze and then lift wheel off floor. Portable with four phenolic swivel casters. Steel construction. Priced and sold as each.

MODEL NUMBER	DESCRIPTION	MAXIMUM TIRE WIDTH	UNIFORM STATIC Capacity (LBS.)	NET WT. (LBS.)
VPJ-9®	VEHICLE JACK	9"	1,500	40
VPJ-12®	VEHICLE JACK	12"	1,500	44
VPJ-DOL	STORAGE DOLLY FC	R HOLDING UP TO	O (4) JACKS	22

Specialty Dollies

Polyethylene Dollies, series DOL, features a steel reinforced structure which gives the dollies a capacity of 1,000 pounds. Available in a flush top or a padded top.

Rolling Knee Dolly, model KNEE-D, is great for people working on their knees. Constructed of red molded plastic with foam cushioned knee cups. Ideal for maintenance departments, automotive garages, and furniture warehouses. Handy tool tray keeps tools in easy reach.

Leg Dolly, model LEG-D, Ideal for moving furniture with legs. Includes swivel hard poly casters. Three foam pads on top of dolly help prevent scratching. Inner cup is 13%" in diameter while the outer cup is 21/4" in diameter. Sold each.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC Capacity (LBS.)	CASTER SIZE	NET WT. (LBS.)
DOL-1830-F®	18" x 30"	10"	1,000	(4) 5"	22
DOL-1830-P®	18" x 30"	10"	1,000	(4) 5"	25
KNEE-D®	20¼" x 10"	3¾"	350	(6) 2"	5
LEG-D®	6 ³ /8" x 5 ³ /4"	21⁄4"	200	(3)1¼"	2

Plastic Dolly with Handle

Plastic Dolly with Handle is made to move boxes, crates and office equipment easily. Strong polyethylene construction will not warp or splinter. Rolls smoothly on (4) polyolefin swivel casters.

MODEL	DECK SIZE	HANDLE	UNIFORM STATIC	WHEEL	NET WT.
NUMBER	(W x L)	Height	Capacity (LBS.)	SIZE	(LBS.)
PDH-1624	16" x 24"	37¼"	500	4" x 1½"	



48 Hours ()to Ship

Plastic Dolly Rubber Ends

Steel reinforced high impact polypropylene construction. Nonporous surface doesn't split, break, rust or become weak. Rubber pads on dolly prevent slipping.

MODEL	DECK SIZE	DECK	UNIFORM STATIC	WHEEL	NET WT.
NUMBER	(W x L)	HEIGHT	Capacity (LBS.)	SIZE	(LBS.)
PDOC-1830	18" x 30"	51⁄2"	1,000	3" x 1¼"	

Plastic Dollies

One piece molded polyethylene dollies are lightweight and easy to clean. Will not rot, warp, dent, or splinter like wood dollies. Ideal for the food service industry. Dollies with pull rope includes 1/4" poly rope handle for easy pulling.

Model POS-1624 features a molded handle. This allows dolly to be easily carried up and down stairs. Unit comes standard with poly-on-poly casters.

Models POS-1830 and POS-2133 roll smoothly on poly-on-poly casters.

MODEL NUMBER	DECK SIZE (W x L)	DECK HEIGHT	UNIFORM STATIC Capacity (LBS.)	WHEEL SIZE	NET WT. (LBS.)
POS-1624	16" x 24"	4½ "	220	3" x 1"	7
POS-1624-ROPE	16" x 24"	4½ "	220	3" x 1"	10
POS-1830	18" x 30"	6"	500	4" x 1¼"	14
POS-1830-ROPE	18" x 30"	6"	500	4" x 1¼"	17
POS-2133	21" x 33"	6"	500	4" x 1¼"	22
POS-2133-ROPE	21" x 33"	6"	500	4" x 1¼"	25

Open Deck Machinery Dolly

Dollies have six high-capacity, abrasion-resistant, cast iron steel wheels on fixed axles to move heavy machinery, containers, and other equipment. The center wheels project lower than end wheels for easier pivoting. Welded steel construction. Model ODMD-2436-6 has a 3" channel steel frame; 5" cast iron wheels have roller bearings. Model ODMD-3660-10 has a 6" channel (1¾" flange width) steel frame; 8" x 3" cast iron wheels have roller bearings. Durable powder coat yellow finish.

MODEL NUMBER	OVERALL SIZE (W x L x H)	CENTER OPENING (W x L)	UNIFORM STATIC Capacity (LBS.)	NET WT. (LBS.)
ODMD-2436-6	24" x 36" x 6 ³ /8"	121/2" x 333/16"	6,000	147
ODMD-3660-10	36" x 60" x 8¼"	24" x 56½"	10,000	370

Low Profile Machinery Dolly

Typically used in pairs or sets of four to move heavy machinery, containers, and other equipment. Deck height is only $1\frac{3}{1}$ " high. Made of all welded steel construction with a $\frac{1}{4}$ " thick deck and $\frac{5}{8}$ " high lip on two sides to retain loads. Four rigid 2" x $\frac{1}{2}$ " steel wheels allow for portability.

MODEL	DECK SIZE	DECK	UNIFORM STATIC	WHEEL	NET WT.
NUMBER	(W x L)	HEIGHT	Capacity (LBS.)	SIZE	(LBS.)
MCD-10®	81⁄2" x 12"	1¾"	10,000	2" x ½"	17

Steel Machine Rollers & Accessories

Made of high-strength annealed ductile iron, these Steel Machine Rollers have swivel tops that rotate 360° on chrome steel ball bearings to allow for easier turning. The rollers form a "tank track" to revolve around a center load bearing plate in the frame to provide maximum maneuverability. The weight of the load is transferred directly from the load bearing plate to the rollers, eliminating axle friction and requiring less power to start and move. A spring loaded locking mechanism on the swivel tops, except on model VHMS-2, can be engaged in detents at 45° intervals. These units are virtually maintenance free. Steering bars split in two and connect with sleeve for easy storage.

MACHINE ROLLERS

MODEL NUMBER	BODY SIZE (W x L)	OVERALL HEIGHT	UNIFORM STATIC Capacity (LBS.)	TYPE OF TOP	NET WT. (LBS.)
VHMS-2	3¼" x 8"	31⁄2"	2,000	SWIVEL	12
VHMS-8	51⁄2" x 10"	5"	8,000	SWIVEL	37
VHMS-15	5¾" x 10½"	5"	15,000	SWIVEL	40
VHMS-30	61⁄2" x 123⁄4"	5"	30,000	SWIVEL	62

MACHINE ROLLER KIT

MODEL		NET WT.
NUMBER	DESCRIPTION	(LBS.)
VHMS-2-KIT	(4) VHMS-2 & (2)VHMH-36-1 STEERING BARS	112

MACHINE ROLLER HANDLES

MODEL NUMBER	DESCRIPTION	USE WITH	HANDLE Length	NET WT. (LBS.)
VHMH-36-1	STEERING BAR	VHMS-2	36"	7
VHMH-48-1	STEERING BAR	VHMS-2	48"	8
VHMH-36-2	STEERING BAR	VHMS-8/15/30	36"	7
VHMH-48-2	STEERING BAR	VHMS-8/15/30	48"	8
VHMH-TB-2	TURNING BAR	VHMS-8/15/30	36"	18





48 Hours





TURNING BAR model VHMH-TB-2











OPTIONAL CORNER

FIXED HEIGHT

TRANSPORTER

model C-FC-40

WITH CAROUSEL

GUARDS model C-AH-4048

ADJUSTABLE HEIGHT TRANSPORTER WITH TILT model C-ATH-4048



ECONOMY FIXED HEIGHT TRANSPORTER WITH OPTIONAL CORNER GUARDS model C-FH-4048



These skates are designed to move heavy equipment and machinery. Nylon wheels are strong and will not mark floors. The top of each skate includes a rubber surface for extra grip. Steel construction with handle to carry and position. Three styles to choose from.

Fixed: Dolly size is nonadjustable and wheels are rigid. Designed primarily for moving in straight lines.

Adjustable: Includes two dollies connected with a slider bar to form one larger dolly. Slider bar allows for adjustable overall dolly width. Designed primarily for moving in straight lines. *Steerable:* Each dolly includes a swivel top plate and a pulling bar to allow for easy maneuvering around turns and corners.

MODEL NUMBER	ROLLER Material	NUMBER OF ROLLERS	OVERALL SIZE (L x W x H)	UNIFORM STATIC Capacity (tons)	NET WT. (LBS.)
FIXED MACHIN	ERY SKATES				
FMS-2.5®	NYLON	2	8¼" x 4" x 4"	2.5	12
FMS-3®	NYLON	4	13" x 11¾" x 4¾"	3	23
FMS-6®	NYLON	6	10¼" x 9" x 4"	6	31
ADJUSTABLE M	ACHINERY SK	ATES			
ASKT-6	NYLON	8	11¾" x 9¾" x 4½"	6	71
ASKT-12	NYLON	12	14" x 8¾" x 4½"	12	88
ASKT-24	STEEL	16	14" x 8¾" x 4½"	24	151
STEERABLE MA	CHINERY SKA	TES			
SSKT-3®	NYLON	4	12¼" x 10" x 4"	3	38
SSKT-6®	NYLON	8	24¾" x 15¾" x 4½"	6	120
SSKT-12®	STEEL	8	24¾" x 15¾" x 4½"	12	168

Steel Dolly Sets

These lightweight steel dollies are ideal for use in hundreds of applications. Each dolly features bolt-on hard rubber swivel casters and a painted finish. V-groove formed deck for strength and slip resistance.

MODEL NUMBER	DECK SIZE (W x L)	DECK Height	UNIFORM STATIC Capacity per set	CASTER SIZE	QUANTITY PER BOX	NET WT. (LBS.)
SDOL-2	8" x 8"	3 ⁵ /8"	500 lbs.	2" x ¾"	2	17
SDOL-4	8" x 8"	3 ⁵ /8"	1,000 lbs.	2" x ¾"	4	33

Heavy-Duty Cradle Carts

Move and store pipe, channel, bar stock, barrels, or drums with these Heavy-Duty Cradle Carts. A large open design that makes loading and unloading by fork trucks and slings easy. All welded construction. Wheels are mounted in a diamond pattern to allow the truck to tilt when going over thresholds and turn about on its own center. Lightweight Aluminum Cradle Cart fits all small to medium loads and rolls on (4) swivel 3" x 1¹/₂" hard rubber casters. The 4,000 & 10,000 pound Steel Cradle Carts rolls on (2) rigid and (2) swivel phenolic casters, except for the DCC-80 which rolls on (4) swivel casters. Powder coat finish standard on steel cart.

MODEL NUMBER	OVERALL SIZE (W x L x H)	UNIFORM STATIC Capacity (LBS.)	CASTER SIZE	NET WT. (LBS.)
DCC-80*	29" x 29" x 24"	4,000	8" x 2"	96
DCC-2860-4*	28" x 60" x 29"	4,000	8" x 2"	203
DCC-2896-4*	28" x 96" x 29"	4,000	8" x 2"	320
DCC-2860-10*	28" x 60" x 29"	10,000	8" x 3"	259
DCC-2896-10*	28" x 96" x 29"	10,000	8" x 3"	550
DCC-28120-10*	28" x 120" x 29"	10,000	8" x 3"	570
DCC-17**	20" x 20" x 516"	600	2" v 11/6"	20

*STEEL CONSTRUCTION / **ALUMINUM CONSTRUCTION, HARD RUBBER CASTERS

Economical Pallet & Container Transporters

Reduce fork truck dependency by transporting pallets and crates to workstations with our Economical Pallet & Container Transporters. Units feature 8" glass-filled nylon casters for easier mobility. Choose from four different styles. Adjustable height models can only be adjusted when unloaded. Order optional corner guides for extra stability (2 come standard with model C-ATH-4048). Steel construction. Powder coat finish.

MODEL NUMBER	SERVICE Range	UNIFORM STATIC Capacity (LBS.)	CASTER Size / Style	NET WEIGHT (POUNDS)			
C-ATH-4048	24" TO 32"	4,000	8" GFN*	205			
C-AH-4048	24" TO 32"	4,000	8" GFN*	190			
C-FH-4048	12"	4,000	8" GFN*	145			
C-FC-40	15"	4,000	8" GFN*	190			
CG-12	OPTIC	OPTIONAL CORNER GUIDE (EACH)					
*GLASS-FILLED NYL	ON						

POWDER COATED

INDUSTRIAL CARTS & DOLLIES

V-Groove Pipe Mover

Pipe and tubing measuring up to 20 feet long may now be easily moved by one person. The V-Groove design keeps loads at the horizontal center of gravity for maximum stability and safety. Large 16" diameter tires will support loads that weigh up to 1,000 pounds. Includes a 37" long handle for added maneuverability. Steel construction. Unit is powder coated blue.

MODEL NUMBER	SIZE (W x L)	HANDLE Length	UNIFORM STATIC Capacity (LBS.)	WHEEL STYLES	NET WT. (LBS.)
VGP-100®	17" x 30"	37"	1,000	PNEUMATIC	108
VGP-100-FF®	17" x 30"	37"	1,000	FOAM FILLED	110

Portable Parts Bin

48 Hours Cut parts picking time in half with these space saving, rotating Parts Bins. Compact enough to fit in small spaces such as corners and ends of aisles. Great for organization of small parts. Ideal for use in commercial and industrial applications. Rugged molded plastic construction with four swivel casters for portability. Each shelf is 21/8" deep. The space between the shelves is 8".

MODEL NUMBER	DIAMETER	DIAMETER HEIGHT		CASTER SIZE	NET WT. (POUNDS)
PBIN-19®	19½"	381/2"	220	3" x ¾"	33

Furniture and Crate Movers

Transport furniture, crates, and machinery easily. Simply slide nose plate under item to be moved, strap both dollies together, and lift. Available in either a manual mechanical hand crank lift option or a manual hand pump hydraulic lift option. Standard with (4) 6" x 2" swivel poly-on-steel casters and 190" long straps. Steel construction with durable paint finish. Priced and sold in pairs. MEM-4000

MODEL	LIFT	PLATE SIZE	UNIFORM	LIFT	OVERALL SIZE	NET WT.
NUMBER	STYLE	(W x D)	CAPACITY	HEIGHT	(W x D x H)	(LBS.)
MFM-1300	MECHANICAL	8¾" x 4¾"	1,300	15"	15½" x 22½" x 30¾"	60
MFM-4000	HYDRAULIC	23½" x 2¼"	4,000	10"	16½" x 26¾" x 42¼"	190

Machinery Lifts

These machinery lifts are the ideal method to move bulky and hard to handle loads. Move large, awkward objects or heavy equipment that is difficult to maneuver or position like refrigerators, safes, furniture, or machines. Yet they are versatile enough to safely handle fragile, sensitive equipment like glass, and computers. Optional side straps secure loads for stable moving. Large wheels allow smooth movement over bumps and cracks of factory floors. Forks are adjustable with mounting pegs to allow for positioning of forks to accommodate different width loads.

MODEL NUMBER	FORKS Adjustable	FORK Length	UNIFORM Capacity	LIFT Height	OVERALL SIZE (W x D x H)	NET WT. (POUNDS)
MFM-2-RAL	71/4" to 171/2"	5"	2,000	5 ¹ /8"	22" x 12½" x 47½"	160
MFM-4-RAL	5" to 191⁄2"	6"	4,000	6"	23" x 16½" x 44"	325
MFM-6-RAL	6" to 191⁄2"	6"	6,000	6"	23" x 16¾" x 42½"	335
MFM-8-RAL	71⁄4" to 191⁄2"	6"	8,000	6"	23" x 17¼" x 45½"	400
MFM-10-RAL	91⁄4" to 191⁄2"	6"	10,000	6"	24" x 18" x 45½"	438
MFM-12-RAL	91⁄4" to 191⁄2"	6"	12,000	6"	24" x 18" x 45½"	470
MFM-BELT-12	BELT WITH TRI	ANGLE HO	OK ENDS, 1	12 FOOT L	ONG	5
MFM-BELT-16	BELT WITH TRI	ANGLE HO	OK ENDS, 1	16 FOOT L	ONG	5
MFM-BELT-20	BELT WITH TRIA	ANGLE HO	OK ENDS, 2	20 FOOT L	ONG	10

Adjustable Height Floor Locks

This one of a kind floor lock includes an adjustable height foot pad that will work on carts with different caster heights. The adjustable height feature provides uniform locking and safety unlocking force for better ergonomic operation. This feature also keeps the floor lock working properly as spring and pads wear over time. Height is adjustable by turning the bottom pad. The bottom pad includes suction-cups for extra grip.

MODEL NUMBER	EXTENDED HEIGHT	RETRACTED HEIGHT	USED WITH CASTER SIZE	NET WT. (LBS.)				
ZINC PLATED FINISH WITH HEAVY-DUTY CAST STEEL CONSTRUCTION								
FL-ADJ-46®	5¾" to 8"	4¾" to 7"	4" - 6"	9				
FL-ADJ-810®	7 ⁵ /8" to 10 ⁷ /8"	61/4" to 91/2"	8" - 10"	11				
STAINLESS STEEL CON	STRUCTION							
FL-ADJ-46-SS℗	5¾" to 8"	4¾" to 7"	4" - 6"	9				
FL-ADJ-810-SS®	7 ⁵ /8" to 10 ⁷ /8"	61⁄4" to 91⁄2"	8" - 10"	11				











model

model

() to Ship

48 Hours to Ship

> 48 Hours to Ship



() to Ship







SIDE MOUNTED FLOOR LOCK model FL-LK-SMR







model FJB-36 shown

Economical Floor Lock

Our economical floor locks help to stabilize mobile equipment during loading and unloading. They are perfect for keeping carts, trucks, work benches and other portable equipment stationary. All of these floor locks are spring loaded and offer a non-skid rubber foot pad to keep equipment stationary. The heavy-duty steel construction has a bright zinc plated finish.

MODEL NUMBER	USE WITH Caster Height	EXTENDED HEIGHT	RETRACTED HEIGHT	TOP PLATE Dimensions	NET WT. (LBS.)
FL-4®	4"	5 ⁷ /8"	5"	4½" x 4"	3
FL-5®	5"	6 ⁵ /8"	5 ⁵ /8"	4½" x 4"	3
FL-6®	6"	7¾"	6 ³ ⁄4"	4½" x 4"	4
FL-8®	8"	9 ¹³ /16"	85/8"	4½" x 4"	4

Low Profile Floor Lock

The lowest-profile floor lock available on the market today. Features adjustable-height pad for precision and wear ability, simply bolt to bottom of cart. Foot operated. Zinc plated finish with heavy-duty cast steel construction.

MODEL EXTENDED		RETRACTED	NET WT.
Number Height		HEIGHT	(LBS.)
FL-LK-LP	4 ³ /8"	37/8"	8

General Purpose Floor Locks

Floor Locks may be used on platform trucks, fixture dollies, or equipment with casters. Simple foot pressure immobilizes equipment. Locks when large friction face is pressed against the floor. To release simply kick release rod. Brake is independent of casters and can be installed to any convenient location on the cart. Vertical mounting plate designed to mount to sides of carts and other portable products. The spring loaded pad accommodates uneven floors. Units mount with pad 11/2" off the floor when retracted.

MODEL NUMBER	MOUNTING Height	RETRACTED HEIGHT	USED WITH CASTER SIZE	NET WT. (LBS.)
FL-LK-5E	6 ⁵ /8"	5 ³ /8"	5"	4
FL-LK-7X	71/4"	6¼"	6"	12
FL-LK-7G	7¾"	6¼"	6"	12
FL-LK-10	9 ¹⁵ / ₁₆ "	8 ⁷ /8"	8"	19
FL-LK-S	7 ³ /8"	4 ¹ /8"	6"	12
FL-LK-SMR	18 ⁷ /16"	15 ¹⁵ /16"	(2" of Travel)	9
STAINLESS STEEL CON	STRUCTION			
FL-LK-SMR-SS	10-15½"	16"	(2" of Travel)	9

Leveling Jacks

Designed for permanent installation, these screw-style jacks hold platforms and other equipment in place and stabilize them at the required height. Drill a 11/4" diameter hole through the platform to be leveled and bolt the platform between the upper and lower flanges of the jack's divided housing. Uniform lifting capacity is 5,000 pounds with a holding capacity of 10,000 pounds. Jacks have an 8¹/₂" long handle that folds down when not in use. 37%" diameter swivel base has a slip-resistant rubber pad on the bottom (replacement pads available). Screw diameter is 11/4". Lift rate is 1/4" per crank revolution.

MODEL NUMBER	MINIMUM EXTENDED HEIGHT	MAXIMUM EXTENDED HEIGHT	OVERALL HEIGHT	SCREW TRAVEL	NET WT. (LBS.)	
STEEL CONSTRUCTION WITH POLISHED CHROME FINISH						
LJ-9®	41⁄2"	131⁄2"	18"	9"	11	
LJ-17®	41⁄2"	21 ½"	26"	17"	14	
LJ-21 🕑	41⁄2"	25½"	30"	21"	16	
STAINLESS STEEL CONSTRUCTION						
LJ-9-SS	41⁄2"	131⁄2"	18"	9"	11	
LJ-17-SS	41⁄2"	21 ½"	26"	17"	14	
LJ-21-SS	41⁄2"	251/2"	30"	21"	16	

REPLACEMENT RUBBER BOTTOM PAD (FOR LJ-SERIES ONLY), MODEL LJ-PAD

REPLACEMENT RUBBER BOTTOM PAD (FOR LJ-SS SERIES ONLY), MODEL LJ-PAD-SS

Basement Floor Jacks

Provide extra support for leveling and stabilizing floor beams and joists during construction and repairs. Telescopic style with removable pins lets you properly position the brace for better leveling. End pad includes a screw and turning bar for easy height adjustment. Rugged all welded steel construction. Red oxide finish.

MODEL NUMBER	MINIMUM HEIGHT	MAXIMUM HEIGHT	MINIMUM HEIGHT CAPACITY (LBS.)	MAXIMUM HEIGHT CAPACITY (LBS.)	NET WT. (LBS.)
FJB-16®	12"	16"	19,475	19,475	7
FJB-36℗	19"	36"	19,475	13,725	12
FJB-100⊛	54"	100"	16,875	11,200	26
FJB-150®	54"	150"	22,400	5,175	37

